

# The MySQL Test Framework

---

# The MySQL Test Framework

## Abstract

This manual describes the MySQL test framework.

Document generated on: 2006-10-18 (revision: 3666)

Copyright 2006 MySQL AB

This documentation is NOT distributed under a GPL license. Use of this documentation is subject to the following terms: You may create a printed copy of this documentation solely for your own personal use. Conversion to other formats is allowed as long as the actual content is not altered or edited in any way. You shall not publish or distribute this documentation in any form or on any media, except if you distribute the documentation in a manner similar to how MySQL disseminates it (that is, electronically for download on a website with the software) or on a CD-ROM or similar medium, provided however that the documentation is disseminated together with the software on the same medium. Any other use, such as any dissemination of printed copies or use of this documentation, in whole or in part, in another publication, requires the prior written consent from an authorized representative of MySQL AB. MySQL AB reserves any and all rights to this documentation not expressly granted above.

Please email [<docs@mysql.com>](mailto:docs@mysql.com) for more information or if you are interested in doing a translation.

---

---

---

---

# Table of Contents

Preface .....	v
1. Introduction .....	1
2. MySQL Test Framework Components .....	3
2.1. The Test Framework and SSL .....	5
2.2. How to Report Bugs in the MySQL Test Suite .....	6
3. Tutorial .....	7
3.1. Running Test Cases .....	7
3.1.1. Constraints on Simultaneous Test Runs .....	8
3.2. Writing a Test Case: Quick Start .....	8
3.3. Writing a Test Case .....	9
3.3.1. Sample Test Case .....	10
3.3.2. Naming Conventions for Database Objects .....	11
3.3.3. Cleaning Up from a Previous Test Run .....	11
3.3.4. Generating a Test Case Result File .....	12
3.3.5. Specifying When Tests are Expected to Fail .....	12
3.3.6. Controlling the Information Produced by a Test Case .....	13
3.3.7. Dealing with Output That Varies Per Test Run .....	14
3.3.8. Specifying Test Case-Specific Server Options .....	16
3.3.9. Other Test Case-Writing Tips .....	16
4. MySQL Test Programs .....	18
4.1. <code>mysqltest</code> — Program to Run Test Cases .....	18
4.2. <code>mysql-test-run.pl</code> — Run MySQL Test Suite .....	21
4.3. <code>mysql-test-run</code> — Run MySQL Test Suite .....	29
4.4. <code>mysql-stress-test.pl</code> — Server Stress Test Program .....	35
5. <code>mysqltest</code> Language Reference .....	38
5.1. <code>mysqltest</code> Input Conventions .....	38
5.2. <code>mysqltest</code> Commands .....	40
5.3. <code>mysqltest</code> Variables .....	50
5.4. <code>mysqltest</code> Flow Control Constructs .....	51
5.5. Error Handling .....	51
6. Creating and Executing Unit Tests .....	53
Index .....	54

---

# Preface

MySQL distributions include a set of test cases and programs for running them. These tools constitute the MySQL test framework that provides a means for verifying that MySQL Server and its client programs operate according to expectations. The test cases consist mostly of SQL statements, but can also use test language constructs that control how to run tests and verify their results.

This manual describes the MySQL test framework. It describes the programs used to run tests and the language used to write test cases.

---

# Chapter 1. Introduction

MySQL distributions include a set of test cases and programs for running them. These tools constitute the MySQL test framework that provides a means for verifying that MySQL Server and its client programs operate according to expectations. The test cases consist mostly of SQL statements, but can also use test language constructs that control how to run tests and verify their results. As of MySQL 5.1, distributions also provide facilities for running unit tests and creating new unit tests.

This document describes the components of the MySQL test framework, how the test programs work, and the language used for writing test cases. It also provides a tutorial for developing test cases and executing them.

The application that runs the test suite is named `mysql-test-run.pl`. Its location is the `mysql-test` directory, which is present both in source and binary MySQL Server distributions.

## Note

There are actually two scripts for running the test suite. `mysql-test-run` is the original shell script and `mysql-test-run.pl` is the newer Perl script. From MySQL 5.1 on, `mysql-test-run.pl` is the preferred script and is, in general, the script name used in discussion and examples throughout this document. If you are using MySQL 5.0 or earlier, substitute `mysql-test-run` appropriately.

The `mysql-test-run.pl` application starts MySQL servers, restarts them as necessary when a specific test case needs different start arguments, and presents the test result. For each test case, `mysql-test-run.pl` invokes the `mysqltest` program (also referred to as the “test engine”) to read the test case file, interpret the test language constructs, and send SQL statements to the server.

Input for each test case is stored in a file, and the expected result from running the test is stored in another file. The expected result can be compared to the actual result produced by running a test to verify proper processing of the input by MySQL.

For a MySQL source distribution, `mysql-test-run.pl` is located in the `mysql-test` directory, and `mysqltest` is located in the `client` directory. The `mysql-test` and `client` directories are located in the root directory of the distribution.

For a MySQL binary distribution, `mysql-test-run.pl` is located in the `mysql-test` directory, and `mysqltest` is located in the same directory where other client programs such as `mysql` or `mysqladmin` are installed. The locations of the `mysql-test` and `client` directories depend on the layout used for the distribution format.

Within the `mysql-test` directory, test case input files and result files are stored in the `t` and `r` directories, respectively. The input and result files have the same basename, which is the test name, but have extensions of `.test` and `.result`, respectively. For example, for a test named “decimal,” the input and result files are `mysql-test/t/decimal.test` and `mysql-test/r/decimal.result`.

Each test file is referred to as one test case, but usually consists of a sequence of related tests. An unexpected failure of a single statement in a test case makes the test fail.

There are several ways a test case can fail:

- The `mysqltest` test engine checks the result codes from executing each SQL statement in the test input. If the failure is unexpected, the test case fails.
- A test case can fail if an error was expected but did not occur (for example, if a SQL statement succeeded when it should have failed).

- The test case can fail by producing incorrect output. As a test runs, it produces output (the results from `SELECT`, `SHOW`, and other statements). This output is compared to the expected result found in the `mysql-test/r` directory (in a file with a `.result` suffix). If the expected and actual results differ, the test case fails. The actual test result is written to a file in the `mysql-test/r` directory with a `.reject` suffix, and the difference between the `.result` and `.reject` files is presented for evaluation.

This method of checking test results puts some restrictions on how test cases can be written. For example, the result cannot contain information that varies from run to run, such as the current time. However, if the information that varies is unimportant for test evaluation, there are ways to instruct the test engine to replace those fields in the output with fixed values.

Because the test cases consist mostly of SQL statements in a text file, there is no direct support for test cases that are written in C, Java, or other languages. Such tests are not within the scope of this test framework. But the framework does support executing your own scripts and initiating them with your own data. Also, a test case can execute an external program, so in some respects the test framework can be extended for uses other than testing SQL statements.

---

# Chapter 2. MySQL Test Framework Components

The MySQL test framework consists of programs that run tests, and directories and files used by those programs.

## Test Framework Programs

The MySQL test framework uses several programs:

- The `mysql-test-run.pl` Perl script is the main application used to run the test suite for MySQL 5.1 and up. It invokes `mysqltest` to run individual test cases.
- The `mysql-test-run` shell script is the main application used to run the test suite before MySQL 5.1. (`mysql-test-run.pl` is preferred as of 5.1.)
- `mysqltest` runs test cases. A version named `mysqltest_embedded` is similar but is built with support for the `libmysqld` embedded server.
- The `mysql-stress-test.pl` Perl script performs stress-testing of the MySQL server. (MySQL 5.0 and up only)
- A unit-testing facility is provided so that individual unit test programs can be created for storage engines and plugins. (MySQL 5.1 and up only)

Except for `mysqltest`, these programs are located in the `mysql-test` directory. `mysqltest` is located elsewhere. For a source distribution, `mysqltest` is in the `client` directory. For a binary distribution, it is in the MySQL `bin` directory.

## Test Framework Directories and Files

The test suite is located in the `mysql-test` directory. For a source distribution, `mysql-test` is found under the source tree root. For a binary distribution, the location of `mysql-test` depends on the layout used for the distribution format.

The `mysql-test` directory contains the following components:

- The `mysql-test-run`, `mysql-test-run.pl`, and `mysql-stress-test.pl` programs that are used for running tests.
- The `t` directory contains test case input files. A test case file might also have option files associated with it.
  - A filename of the form `test_name.test` is a test case file for a test named `test_name`. For example, `subselect.test` is the test case file for the test named `subselect`.
  - A filename of the form `test_name-master.opt` provides options to associate with the named test case. `mysql-test-run.pl` restarts the server with the options given in the file if the options are different from those required for the currently running server.

Note that the `-master.opt` file is used for the “main” server of a test, even if no replication is involved.

- A filename of the form `test_name-slave.opt` provides slave options.



- A filename of the form `test_name-im.opt` provides Instance Manager options.
- The `disabled.def` file contains information about deferred/disabled tests. When a test is failing because of a bug in the server and you want it to be ignored by `mysql-test-run.pl`, list the test in this file.

The format of a line in the `disabled.def` file looks like this, where fields are separated by one or more spaces (Tab characters are not allowed):

```
test_name : BUG#nnnnn YYYY-MM-DD disabler comment
```

Example:

```
rpl_row_blob_innodb : Bug#18980 [http://bugs.mysql.com/18980] 2006-04-10 kent Test fails random
```

`test_name` is the test case name. `BUG#nnnnn` indicates the bug related to the test that causes it to fail (and thus requires it to be disabled). `disabler` is the name of the person that disabled the test. `comment` normally provides a reason why the test was disabled.

A comment line can be written in the file by beginning the line with a '#' character.

- The `r` directory contains test case result files:
  - A filename of the form `test_name.result` is the expected result for the named test case. A file `r/test_name.result` is the output that corresponds to the input in the test case file `t/test_name.test`.
  - A filename of the form `test_name.reject` contains output for the named test case if the test fails.

For a test case that succeeds, the `.result` file represents both the expected and actual result. For a test case that fails, the `.result` file represents the expected result, and the `.reject` file represents the actual result.

If a `.reject` file is created because a test fails, `mysql-test-run.pl` removes the file later the next time the test succeeds.

- The `include` directory contains files that are included by test case files using the `source` command.
- The `lib` directory contains library files used by `mysql-test-run.pl`, and database initialization SQL code.
- The `std_data` directory contains data files used by some of the tests.
- The `var` directory is used during test runs for various kinds of files: log files, temporary files, trace files, Unix socket files for the servers started during the tests, and so forth. This directory cannot be shared by simultaneous test runs.

Unit test-related files are located in the `unittest` directory. Additional files specific to storage engines and plugins may be present under the subdirectories of the `storage` or `plugin` directories.

### Test Execution and Evaluation

There are a number of targets in the top-level `Makefile` that can be used to run sets of tests. `make test` runs all the tests. Other targets run subsets of the tests, or run tests with specific options for the

test programs. Have a look at the [Makefile](#) to see what targets are available.

A “test case” is a single file. The case might contain multiple individual test commands. If any individual command fails, the entire test case is considered to fail. Note that “fail” means “does not produce the expected result.” It does *not* necessarily mean “executes without error,” because some tests are written precisely to verify that an illegal statement does in fact produce an error. In such an instance, if the statement executes successfully without producing the expected error, that is considered failure of the test.

Test case output (the test result) consists of:

- Input SQL statements and their output. Each statement is written to the result followed by its output. Columns in output resulting from SQL statements are separated by tab characters.
- The result from `mysqltest` commands such as `echo` and `exec`. The commands themselves are not echoed to the result, only their output.

The `disable_query_log` and `enable_query_log` commands control logging of input SQL statements. The `disable_result_log` and `enable_result_log` commands control logging of SQL statement results, and warning or error messages resulting from those statements.

`mysqltest` reads a test case file from its standard input by default. The `--test-file` or `-x` option can be given to name a test case file explicitly.

`mysqltest` writes test case output to the standard output by default. The `--result-file` or `-R` option can be used to indicate the location of the result file. That option, together with the `--record` option, determine how `mysqltest` treats the test actual and expected results for a test case:

- If the test produces no results, `mysqltest` exits with an error message to that effect.
- Otherwise, if `--result-file` is not given, `mysqltest` sends test results to the standard output.
- With `--result-file` but not `--record`, `mysqltest` reads the expected results from the given file and compares them with the actual results. If the results do not match, `mysqltest` writes a `.reject` file in the same directory as the result file and exits with an error.
- With both `--result-file` and `--record`, `mysqltest` updates the given file by writing the actual test results to it.

`mysqltest` itself knows nothing of the `t` and `r` directories under the `mysql-test` directory. The use of files in those directories is a convention that is used by `mysql-test-run.pl`, which invokes `mysqltest` with the appropriate options for each test case to tell `mysqltest` where to read input and write output.

## 2.1. The Test Framework and SSL

When `mysql-test-run.pl` starts, it checks whether `mysqld` supports SSL connections:

- If `mysqld` supports SSL, `mysql-test-run.pl` starts it with the proper `--ssl-xxx` options that enable it to accept SSL connections for those test cases that require secure connections (those with “ssl” in their name). As `mysql-test-run.pl` runs test cases, a secure connection to `mysqld` is initiated for those cases that require one. For those test cases that do not require SSL, an unencrypted connection is initiated.
- If `mysqld` does not support SSL, `mysql-test-run.pl` skips those test cases that require secure

connections.

If `mysql-test-run.pl` is started with the `--ssl` option, it sets up a secure connection for all test cases. In this case, if `mysqld` does not support SSL, `mysql-test-run.pl` exits with an error message: `Couldn't find support for SSL`

For `mysql-test-run` (the shell version), the `--with-openssl` option corresponds to the `--ssl` option for `mysql-test-run.pl`.

## 2.2. How to Report Bugs in the MySQL Test Suite

If test cases from the test suite fail, you should do the following:

- Do not file a bug report before you have found out as much as possible about what when wrong. See the instructions at <http://dev.mysql.com/doc/mysql/en/bug-reports>.
- Make sure to include the output of `mysql-test-run`, as well as contents of all `.reject` files in the `mysql-test/r` directory.
- Check whether an individual test in the test suite also fails when run on its own:

```
shell> cd mysql-test
shell> ./mysql-test-run.pl test_name
```

If this fails, you should configure MySQL with `--with-debug` and run `mysql-test-run` with the `--debug` option. If this also fails, send the trace file `mysql-test/var/tmp/master.trace` to <ftp://ftp.mysql.com/pub/mysql/upload/> so that we can examine it. Please remember to also include a full description of your system, the version of the `mysqld` binary and how you compiled it.

- Run `mysql-test-run` with the `--force` option to see whether any other tests fail.
- If you have compiled MySQL yourself, check the MySQL Reference Manual to see whether there are any platform-specific issues for your system. There might be configuration workarounds to deal with the problems that you observe. Also, consider using one of the binaries we have compiled for you at <http://dev.mysql.com/downloads/>. All our standard binaries should pass the test suite!
- If you get an error such as `Result length mismatch` or `Result content mismatch` it means that the output of the test was not an exact match for the expected output. This could be a bug in MySQL or it could be that your version of `mysqld` produces slightly different results under some circumstances.

The results file is located in the `r` directory and has a name with a `.result` extension. A failed test result is put in a file with the same basename as the result file and a `.reject` extension. If your test case is failing, you should use `diff` to compare the `.result` and `.reject` files. If you cannot see how they are different, examine both with `od -c` and also check their lengths.

- If a test fails completely, you should check the logs file in the `mysql-test/var/log` directory for hints of what went wrong.
- If you have compiled MySQL with debugging, you can try to debug test failures by running `mysql-test-run` with either or both of the `--gdb` and `--debug` options.

If you have not compiled MySQL for debugging you should probably do so by specifying the `--with-debug` option when you invoke `configure`.

---

# Chapter 3. Tutorial

[This chapter is based on the information that was in the Wiki, so some of it probably is outdated.]

Normally, you run the test suite during the development process to ensure that your changes do not cause existing test cases to break. You can also write new test cases or add tests to existing cases. This happens when you fix a bug (so that the bug cannot reappear later without being detected) or when you add new capabilities to the server or other MySQL programs.

This chapter provides a tutorial on running existing test cases for the MySQL test framework and developing new test cases.

## 3.1. Running Test Cases

Typically, you run the test suite either from within a source tree (after MySQL has been built), or on a host where the MySQL server distribution has been installed. To run tests, your current working directory should be the `mysql-test` directory of your source tree or installed distribution. In a source distribution, `mysql-test` is under the root of the source tree. In a binary distribution, the location of `mysql-test` depends on the distribution layout. The program that runs the test suite, `mysql-test-run.pl`, will figure out whether you are in a source tree or an installed directory tree.

To run the test suite, change location into your `mysql-test` directory and invoke the `mysql-test-run.pl` script:

```
shell> cd mysql-test
shell> ./mysql-test-run.pl
```

`mysql-test-run.pl` accepts options on the command line. For example:

```
shell> ./mysql-test-run.pl --force --local
```

By default, `mysql-test-run.pl` exits if a test case fails. `--force` causes execution to continue regardless of test case failure.

The `--local` option tells `mysql-test-run.pl` not to use an already running server, but to start a server itself to use for the tests. This option is the default as of MySQL 4.1, so it is necessary only before 4.1.

For a full list of the supported options, see [Section 4.2, “mysql-test-run.pl — Run MySQL Test Suite”](#).

To run one or more specific test cases, name them on the `mysql-test-run.pl` command line. Test case files have names like `t/test_name.test`, where `test_name` is the name of the test case, but each name given on the command line should be the test case name, not the full test case filename. The following command runs the test case named `rpl_abcd`, which has a test file of `t/rpl_abcd.test`:

```
shell> ./mysql-test-run.pl rpl_abcd
```

To run a family of test cases for which the names share a common prefix, use the `--do-tests` option:

```
shell> ./mysql-test-run.pl --do-test=prefix
```

For example, the following command runs the replication tests (test cases that have names beginning with `rpl`):

```
shell> ./mysql-test-run.pl --do-tests=rpl
```

`mysql-test-run.pl` starts the MySQL server if necessary, sets up the environment for calling the `mysqltest` program, and invokes `mysqltest` to run the test case. For each test case to be run, `mysqltest` handles operations such as reading input from the test case file, starting managers, creating server connections, and sending SQL statements to servers.

The language used in test case files is a mix of commands that the `mysqltest` program understands and SQL statements. Input that `mysqltest` doesn't understand is assumed to consist of SQL statements to be sent to the database server. This makes the test case language familiar to those that know how to write SQL and powerful enough to add the control needed to write test cases.

You need not start a MySQL server first before running tests. Instead, the `mysql-test-run.pl` program will start the server or servers needed on ports that do not conflict with ports used a production server, if you happen to have one on the same machine. (The test run uses ports in the range around 9300, so production servers should not use ports in that range.)

### 3.1.1. Constraints on Simultaneous Test Runs

If you have multiple users that run tests simultaneously on the same machine, you must specify to the `mysql-test-run.pl` program which ports to use so that no test run conflicts with others running concurrently. You add unique port arguments to `mysql-test-run.pl`, such as `--no-manager --master_port=3911 --slave_port=3927`.

Only one person at a time can run the `mysql-test-run.pl` program in the same `mysql-test` directory on a shared drive. The `mysql-test/var` directory created and used by `mysql-test-run.pl` cannot be shared between simultaneous test runs. A test run can use the `--var=dir_path` option to specify an alternate directory not used by other runs.

## 3.2. Writing a Test Case: Quick Start

The basic principle of test case evaluation is that output resulting from running a test case is compared to the expected result. This is just a `diff` comparison between the output and an expected-result file that the test writer provides. This simplistic method of comparison does not by itself provide any way to handle variation in the output that may occur when a test is run at different times. However, the test language provides commands for postprocessing result output before the comparison occurs. This enables you to manage certain forms of expected variation.

Use the following procedure to write a new test case. In the examples, `test_name` represents the name of the test case. It's assumed here that you'll be using a development source tree, so that when you create a new test case, you can commit the files associated with it to the source repository for others to use.

1. Change location to the test directory `mysql-version/mysql-test`:

```
shell> cd mysql-version/mysql-test
```

`mysql-version` represents the root directory of your source tree, such as `mysql-5.0` or `mysql-5.1`.

2. Create the test case in a file `t/test_name.test`. You can do this with any text editor. For details of the language used for writing `mysqltest` test cases, see [Chapter 5, \*mysqltest Language Reference\*](#).
3. Create an empty result file:

```
shell> touch r/test_name.result
```

4. Run the test:

```
shell> ./mysql-test-run.pl test_name
```

5. Assuming that the test case produces output, it should fail because the output does not match the result file (which is empty at this point). The failure results in creation of a reject file named `r/test_name.reject`. Examine this file. If the reject file appears to contain the output that you expect the test case to produce, copy its content to the result file:

```
shell> cp r/test_name.reject r/test_name.result
```

Another way to create the result file is by invoking `mysql-test-run.pl` with the `--record` option to record the test output in the result file:

```
shell> ./mysql-test-run.pl --record test_name
```

6. Run the test again. This time it should succeed:

```
shell> ./mysql-test-run.pl test_name
```

You can also run the newly created test case as part of the entire suite:

```
shell> ./mysql-test-run.pl
```

It is also possible to invoke the `mysqltest` program directly. If the test case file refers to environment variables, you will need to define those variables in your environment first. For more information about the `mysqltest` program, see [Section 4.1, “mysqltest — Program to Run Test Cases”](#).

## 3.3. Writing a Test Case

To write a test case file, use any text editor that uses linefeed (newline) as the end-of-line character. The filename should be lowercase ASCII with no spaces.

We are adding support for multiple test “suites.” Until then, all test cases must be located in the `mysql-test/t` directory. Test case filenames consist of the test name with a `.test` suffix. For example, a test named `foo` should be written in the file `mysql-test/t/foo.test`.

### Note

All our test cases are published on the Internet. Take care that their contents include no confidential information.

One test case file can be a collection of individual tests that belong together. If one of the tests fails, the entire test case fails. Although it may be tempting to write each small test into a single file, that will be too inefficient and makes test runs unbearably slow. So make the test case files not too big, not too small.

Some definitions:

- One “test file” is one “test case.”
- One “test case” might contain a “test sequence” (that is, a number of individual tests that are grouped

together in the same test file).

- A “command” is an input test that `mysqltest` recognizes and executes itself. A “statement” is an SQL statement or query that `mysqltest` sends to the MySQL server to be executed.

Each test case (that is, each test file) must be self contained and independent of other test cases. Do not create or populate a table in one test case and depend on the table in a later test case. If you have some common initialization that needs to be done for multiple test cases, create an include file. That is, create a file containing the initialization code in the `mysql-test/include` directory, and then put a `source` command in each test case that requires the code. For example, if several test cases need to have a given table created and filled with data, put the statements to do that in a file named `mysql-test/include/create_my_table.inc`. Then put the following command in each test case file that needs the initialization code:

```
--source include/create_my_table.inc
```

The filename in the `source` command is relative to the `mysql-test` directory.

A comment in a test case can be started with the ‘#’ character or the ‘--’ characters. However, if the first word after the ‘--’ is a word that `mysqltest` recognizes as a command, `mysqltest` will execute the comment as a command. For this reason, it is safest to use the ‘#’ character for comments, so as not to accidentally execute a `mysqltest` command. For example, `-- End of test 43` begins with the ‘--’ characters, but will result in an error message because `end` is something that `mysqltest` thinks is a command.

[Section 5.1, “mysqltest Input Conventions”](#), discusses the details of input syntax for `mysqltest` test cases.

### 3.3.1. Sample Test Case

Here is a small sample test case:

```
--disable_warnings
DROP TABLE IF EXISTS t1;
--enable_warnings
SET SQL_WARNINGS=1;

CREATE TABLE t1 (a INT);
INSERT INTO t1 VALUES (1);
INSERT INTO t1 VALUES ("hej");
```

The first few lines try to clean up from possible earlier runs of the test case by dropping the `t1` table. The test case uses `disable_warnings` to prevent warnings from being written to the output because it is not of any interest at this point during the test to know whether the table `t1` was there. After dropping the table, the test case uses `enable_warnings` so that subsequent warnings will be written to the output. The test case also enables verbose warnings in MySQL using the `SET SQL_WARNINGS=1;` statement.

Next, the test case creates the table `t1` and tries some operations. Creating the table and inserting the first row are operations that should not generate any warnings. The second insert should generate a warning because it inserts a non-numeric string into a numeric column. The output that results from running the test looks like this:

```
DROP TABLE IF EXISTS t1;
SET SQL_WARNINGS=1;
CREATE TABLE t1 (a INT);
INSERT INTO t1 VALUES (1);
INSERT INTO t1 VALUES ("hej");
Warnings:
Warning 1265      Data truncated for column 'a' at row 1
```

Note that the result includes not only the output from SQL statements, but the statements themselves. Statement logging can be disabled with the `disable_query_log` test language command. There are several options for controlling the amount of output from running the tests.

If there was a test failure, it will be reported to the screen. You can see the actual output from the last unsuccessful run of the test case in the reject file `r/test_name.reject`.

### 3.3.2. Naming Conventions for Database Objects

It is possible to run test cases against a production server. (Generally, we will not do that, but our customers might.) To reduce the risk that running the test suite alters or destroys important tables, views, or other objects, you should create them using the following naming conventions:

- Table names: `t1`, `t2`, `t3`, ...
- View names: `v1`, `v2`, `v3`, ...

For examples of how to name objects, examine the existing test cases. Of course, you can name columns and other objects inside tables as you wish.

Unless you have a special reason not to, use the default database named `test` that is already created for you.

### 3.3.3. Cleaning Up from a Previous Test Run

For efficiency, the `mysqltest` test engine does not start with a clean new database for running each test case, so a test case generally starts with a “cleaning up section.” Assume that a test case will use two tables named `t1` and `t2`. The test case should begin by making sure that any old tables with those names do not exist:

```
#
# Test of XXXXX
#
--disable_warnings
drop table if exists t1,t2;
--enable_warnings
```

The `disable_warnings` command instructs the test engine not to log any warnings until an `enable_warnings` command occurs or the test case is ended. (MySQL generates a warning if the table `t1` or `t2` does not exist.) Surrounding this part of the test case with commands to disable and enable warnings makes its output the same regardless of whether the tables exist before the test is started. After ensuring that the tables do not exist, we are free to put in any SQL statements that create and use the tables `t1` and `t2`. The test case should also clean up at the end of the test by dropping any tables that it creates.

Let's put in some SQL code into this test case:

```
create table t1 (
  Period smallint(4) unsigned zerofill default '0000' not null,
  Varor_period smallint(4) unsigned default '0' not null
);
create table t2 (Period smallint);

insert into t1 values (9410,9412);
insert into t2 values (9410),(9411),(9412),(9413);

select period from t1;
select * from t1;
```



```
select t1.* from t1;
select * from t1 inner join t2 using (Period);

drop table t1, t2;
```

### 3.3.4. Generating a Test Case Result File

The test code we just wrote contains no checks of the result. The test will report a failure for one of two reasons:

- An individual SQL statement fails with an error
- The overall test case result does not match what was expected

In the first case, `mysqltest` aborts with an error. The second case requires that we have a record of the expected result so that it can be compared with the actual result. To generate a file that contains the test result, run the test with the `--record` option, like this:

```
shell> cd mysql-test
shell> ./mysql-test-run.pl --record foo
```

Running the test as shown creates a result file named `mysql-test/r/foo.result` that has this content:

```
drop table if exists t1,t2;
create table t1 (
  Period smallint(4) unsigned zerofill default '0000' not null,
  Varor_period smallint(4) unsigned default '0' not null
);
create table t2 (Period smallint);
insert into t1 values (9410,9412);
insert into t2 values (9410),(9411),(9412),(9413);
select period from t1;
period
9410
select * from t1;
Period Varor_period
9410 9412
select t1.* from t1;
Period Varor_period
9410 9412
select * from t1 inner join t2 using (Period);
Period Varor_period
9410 9412
drop table t1, t2;
ok
```

If we look at this result file, it contains the statements in the `foo.test` file together with the output from the `SELECT` statements. The output for each statement includes a row of column headings followed by data rows. Rows have columns separated by Tab characters.

At this point, you should inspect the result file and determine whether its contents are as expected. If so, let it be part of your test case. If the result is not as expected, you have found a problem, either with the server or the test. Determine the cause of the problem and fix it. For example, the test might produce output that varies from run to run. To deal with this, you can postprocess the output before the comparison occurs. See [Section 3.3.7, “Dealing with Output That Varies Per Test Run”](#).

### 3.3.5. Specifying When Tests are Expected to Fail

A good test suite checks not only that operations succeed as they ought, but also that they fail as they ought. For example, if a statement is illegal, the server should reject it with an error message. The test

suite should verify that the statement fails and that it fails with the proper error message.

The test engine enables you to specify “expected failures.” Let's say that after we create `t1`, we try to create it again without dropping it first:

```
--disable_warnings
drop table if exists t1,t2;
--enable_warnings
create table t1 (
  Period smallint(4) unsigned zerofill default '0000' not null,
  Varor_period smallint(4) unsigned default '0' not null
);
create table t2 (Period smallint);

insert into t1 values (9410,9412);
insert into t2 values (9410),(9411),(9412),(9413);

select period from t1;
select * from t1;
select t1.* from t1;
select * from t1 inner join t2 using (Period);

create table t1 (something smallint(4));
```

The result is failure and an error:

```
At line 21: query 'create table t1 (something smallint(4))'
failed: 1050: Table 't1' already exists
```

To handle this error and indicate that indeed we do expect MySQL error code 1050 to occur, we can put an `error` command before the second `create table` statement:

```
--error 1050
```

After we make this change and run the test again, the end of the result will look like this:

```
create table t1 (something smallint(4));
ERROR 42S01: Table 't1' already exists
```

In this case, the result shows the statement that causes the error, together with the resulting error message. The fact that `mysqltest` does not terminate and that the error message becomes part of the result indicates that the error was expected.

Note: 1050 is the numeric MySQL error number, and 42S01 is the corresponding SQLSTATE value. If you like, you can specify SQLSTATE values in `error` commands by using an `S` prefix:

```
--error S42S01
```

It is also possible to specify errors by means of the symbolic name from `mysqld_error.h`:

```
--error ER_TABLE_EXISTS_ERROR
```

### 3.3.6. Controlling the Information Produced by a Test Case

By default, the `mysqltest` test engine produces output only from `select`, `show`, and other SQL statements that you expect to produce output (that is, statements that create a result set). It also produces output from certain commands such as `echo` and `exec`. `mysqltest` can be instructed to be more or less verbose.

Suppose that we want to include in the result the number of rows affected by or returned by SQL statements. To do this, add the following line to the test case file preceding the first table-creation statement:

```
--enable_info
```

After rerunning the test by invoking `mysql-test-run.pl` with the `--record` option to record the new result, the result file will contain more information:

```
drop table if exists t1,t2;
create table t1 (
  Period smallint(4) unsigned zerofill default '0000' not null,
  Varor_period smallint(4) unsigned default '0' not null
);
affected rows: 0
create table t2 (Period smallint);
affected rows: 0
insert into t1 values (9410,9412);
affected rows: 1
insert into t2 values (9410),(9411),(9412),(9413);
affected rows: 4
info: Records: 4 Duplicates: 0 Warnings: 0
select period from t1;
period
9410
affected rows: 1
select * from t1;
Period Varor_period
9410 9412
affected rows: 1
select t1.* from t1;
Period Varor_period
9410 9412
affected rows: 1
select * from t1 inner join t2 using (Period);
Period Varor_period
9410 9412
affected rows: 1
drop table t1, t2;
affected rows: 0
ok
```

To turn off the affected-rows reporting, add this command to the test case file:

```
--disable_info
```

In general, options can be enabled and disabled for different parts of the test file. Suppose that we are interested in the internals of the database as well. We could enable the display of query metadata using [enable\\_metadata](#). With this option enabled, the test output is a bit verbose. However, as mentioned earlier, the option can be enabled and disabled selectively so that it is enabled only for those parts of the test case where it interests you to know more.

If you perform an operation for which you have no interest in seeing the statements logged to the result, you can disable statement logging. For example, you might be initializing a table where you don't really expect a failure, and you are not interested in seeing the initialization statements in the test result. You can use the [disable\\_query\\_log](#) command to temporarily disable recording of input SQL statements, and enable recording again with [enable\\_query\\_log](#). You can disable the recording of the output from executing commands using [disable\\_result\\_log](#) and enable recording again with [enable\\_result\\_log](#).

### 3.3.7. Dealing with Output That Varies Per Test Run

It is best to write each test case so that the result it produces does not vary for each test run, or according to factors such as the time of day, differences in how program binaries are compiled, the operating system, and so forth. For example, if the result contains the current date and time, the test engine has no way to verify that the result is correct.

However, sometimes a test result is inherently variable according to external factors, or perhaps there is a part of a result that you simply do not care about. `mysqltest` provides commands that enable you to

postprocess test output into a more standard format so that output variation across test runs will not trigger a result mismatch.

One such command is `replace_column`, which specifies that you want to replace whatever is in a given column with a string. This makes the output for that column the same for each test run.

To see how this command works, add the following row after the first insert in the test case:

```
insert into t1 values (date_format(now(), '%s'),9999);
```

Then record the test result and run the test again:

```
shell> ./mysql-test-run.pl --record foo
shell> ./mysql-test-run.pl foo
```

Most likely, a failure will occur and `mysql-test-run.pl` will display the difference between the expected result and what we actually got, like this:

Below are the diffs between actual and expected results:

```
-----
*** r/foo.result          Thu Jan 20 18:38:37 2005
--- r/foo.reject         Thu Jan 20 18:39:00 2005
*** 16,32 ****
    select period from t1;
    period
    9410
! 0034
    affected rows: 2
    select * from t1;
    Period Varor_period
    9410 9412
! 0034 9999
    affected rows: 2
    select t1.* from t1;
    Period Varor_period
    9410 9412
! 0034 9999
    affected rows: 2
    select * from t1 inner join t2 using (Period);
    Period Varor_period
--- 16,32 ----
    select period from t1;
    period
    9410
! 0038
    affected rows: 2
    select * from t1;
    Period Varor_period
    9410 9412
! 0038 9999
    affected rows: 2
    select t1.* from t1;
    Period Varor_period
    9410 9412
! 0038 9999
    affected rows: 2
    select * from t1 inner join t2 using (Period);
    Period Varor_period
-----
```

If we are not really interested in the first column, one way to eliminate this mismatch is by using the `replace_column` command. The duration of the effect of this command is the next SQL statement, so we need one before each `select` statement:

```
--replace_column 1 SECONDS
select period from t1;
--replace_column 1 SECONDS
select * from t1;
--replace_column 1 SECONDS
select t1.* from t1;
```

In the `replace_column` commands, `SECONDS` could be any string. Its only purpose is to map variable output onto a constant value. If we record the test result again, we will succeed each time we run the test after that. The result file will look like this:

```
drop table if exists t1,t2;
create table t1 (
  Period smallint(4) unsigned zerofill default '0000' not null,
  Varor_period smallint(4) unsigned default '0' not null
);
affected rows: 0
create table t2 (Period smallint);
affected rows: 0
insert into t1 values (9410,9412);
affected rows: 1
insert into t1 values (date_format(now(), '%s'),9999);
affected rows: 1
insert into t2 values (9410),(9411),(9412),(9413);
affected rows: 4
info: Records: 4 Duplicates: 0 Warnings: 0
select period from t1;
period
SECONDS
SECONDS
affected rows: 2
select * from t1;
Period Varor_period
SECONDS 9412
SECONDS 9999
affected rows: 2
select t1.* from t1;
Period Varor_period
SECONDS 9412
SECONDS 9999
affected rows: 2
select * from t1 inner join t2 using (Period);
Period Varor_period
9410 9412
affected rows: 1
drop table t1, t2;
affected rows: 0
ok
```

### 3.3.8. Specifying Test Case-Specific Server Options

Many server options can be set from within test cases by using statements such as these:

```
set sql_warnings=1;
set sql_mode=no_auto_value_on_zero;
```

But sometimes you need to restart the server to use options in the form of extra command-line options. You can specify these options in a file named `mysql-test/t/test_name-master.opt`. When a file named `t/test_name-master.opt` exists, `mysql-test-run.pl` examines it for extra options that the server needs to be run with when executing the `test_name` test case. If no server has yet been started or the current server is running with different options, `mysql-test-run.pl` restarts the server with the new options.

Files in the `mysql-test/t` directory with names ending in `-slave.opt` and `-im.opt` are similar, but they are used for slave servers and the Instance Manager, respectively.

### 3.3.9. Other Test Case-Writing Tips

- If you are writing a replication test case, the first line of the test file should be `source include/master-slave.inc`. To switch between master and slave, use `connection master`; and `connection slave`;. If you need to do something on an alternative connection, you can do `connection master1`; for the master, and `connection slave1`; for the slave.

- If you need to do something in a loop, you can use something like this:

```
let $1=1000;
while ($1)
{
  # execute your statements here
  dec $1;
}
```

- To sleep between statements, use the `sleep` command. It supports fractions of a second. For example, `sleep 1.3;` sleeps 1.3 seconds. Try not to use `sleep` or `real_sleep` commands more than necessary. The more of them there are, the slower the test suite becomes.
- To run the slave with additional options for your test case, put them in the command-line format in `mysql-test/t/test_name-slave.opt`. For the master, put them in `mysql-test/t/test_name-master.opt`.

---

# Chapter 4. MySQL Test Programs

This chapter describes the test programs that run test cases. For information about the language used for writing test cases, see [Chapter 5, \*mysqltest Language Reference\*](#).

The test suite uses the following programs:

- The `mysql-test-run.pl` Perl script is the main application used to run the test suite for MySQL 5.1 and up. It invokes `mysqltest` to run individual test cases.
- The `mysql-test-run` shell script is the main application used to run the test suite before MySQL 5.1. (`mysql-test-run.pl` is preferred as of 5.1.)
- `mysqltest` runs test cases. A version named `mysqltest_embedded` is similar but is built with support for the `libmysqld` embedded server.
- The `mysql-stress-test.pl` Perl script performs stress-testing of the MySQL server. (MySQL 5.0 and up only)

## 4.1. `mysqltest` — Program to Run Test Cases

The `mysqltest` program runs a test case against a MySQL server and optionally compares the output with a result file. This program reads input written in a special test language. Typically, you invoke `mysqltest` via `mysql-test-run.pl` rather than invoking it directly.

Features of `mysqltest`:

- Can send SQL statements to MySQL servers for execution
- Can execute external shell commands
- Can test whether the result from a SQL statement or shell command is as expected
- Can connect to one or more standalone `mysqld` servers and switch between connections
- Can connect to an embedded server (`libmysqld`), if MySQL is compiled with support for `libmysqld`. (In this case, the executable is named `mysqltest_embedded` rather than `mysqltest`.)

By default, `mysqltest` reads the test case on the standard input. To run `mysqltest` this way, you normally invoke it like this:

```
shell> mysqltest [options] [db_name] < test_file
```

You can also name the test case file with a `--test-file=file_name` option.

`mysqltest` supports the following options:

- `--help, -?`

Display a help message and exit.

- `--basedir=dir_name, -b dir_name`  
The base directory for tests.
- `--big-test, -B`  
Define the `mysqltest` variable `$BIG_TEST` as 1.
- `--compress, -C`  
Compress all information sent between the client and the server if both support compression.
- `--cursor-protocol`  
Use cursors for prepared statements (implies `--ps-protocol`). This option was added in MySQL 5.0.19.
- `--database=db_name, -D db_name`  
The default database to use.
- `--debug[=debug_options], -#[debug_options]`  
Write a debugging log if MySQL is built with debugging support. The default `debug_options` value is `'d:t:S:i:O,/tmp/mysqltest.trace'`.
- `--host=host_name, -h host_name`  
Connect to the MySQL server on the given host.
- `--include=file_name, -i file_name`  
Include the contents of the given file before processing the contents of the test file. The included file should have the same format as other `mysqltest` test files. This option has the same effect as putting a `--source file_name` command as the first line of the test file. This option was added in MySQL 5.1.7.
- `--max-connect-retries=num`  
The maximum number of connection attempts when connecting to server. This option was added in MySQL 5.0.23.
- `--no-defaults`  
Do not read default options from any option files.
- `--password[=password], -p[password]`  
The password to use when connecting to the server. If you use the short option form (`-p`), you *cannot* have a space between the option and the password. If you omit the `password` value following the `--password` or `-p` option on the command line, you are prompted for one.
- `--port=port_num, -P port_num`  
The TCP/IP port number to use for the connection.
- `--ps-protocol`  
Use the prepared-statement protocol for communication.



- `--quiet`

Suppress all normal output. This is a synonym for `--silent`.

- `--record, -r`

Record the output that results from running the test file into the file named by the `--result-file` option, if that option is given.

- `--result-file=file_name, -R file_name`

This option specifies the file for test case expected results. `--result-file`, together with `--record`, determines how `mysqltest` treats the test actual and expected results for a test case:

- If the test produces no results, `mysqltest` exits with an error message to that effect.
  - Otherwise, if `--result-file` is not given, `mysqltest` sends test results to the standard output.
  - With `--result-file` but not `--record`, `mysqltest` reads the expected results from the given file and compares them with the actual results. If the results do not match, `mysqltest` writes a `.reject` file in the same directory as the result file and exits with an error.
  - With both `--result-file` and `--record`, `mysqltest` updates the given file by writing the actual test results to it.
- `--server-arg=value, -A value`

Pass the argument as an argument to the embedded server. For example, `--server-arg=--tmpdir=/tmp` or `--server-arg=--core`. Up to 64 arguments can be given.

- `--server-file=file_name, -F file_name`

Read arguments for the embedded server from the given file. The file should contain one argument per line.

- `--silent, -s`

Suppress all normal output.

- `--skip-safemalloc`

Do not use memory allocation checking.

- `--sleep=num, -T num`

Cause all `sleep` commands in the test case file to sleep `num` seconds. This option does not affect `real_sleep` commands.

As of MySQL 5.0.23, an option value of 0 can be used, which effectively disables `sleep` commands in the test case.

- `--socket=path, -S path`

The socket file to use when connecting to `localhost` (which is the default host).

- `--sp-protocol`

Execute DML statements within a stored procedure. For every DML statement, `mysqltest` creates

and invokes a stored procedure that executes the statement rather than executing the statement directly. This option was added in MySQL 5.0.19.

- `--test-file=file_name, -x file_name`

Read test input from this file. The default is to read from the standard input.

- `--timer-file=file_name, -m file_name`

The file where the timing in microseconds is written.

- `--tmpdir=dir_name, -t dir_name`

The temporary directory where socket files are put.

- `--user=user_name, -u user_name`

The MySQL username to use when connecting to the server.

- `--verbose, -v`

Verbose mode. Print out more information what the program does.

- `--version, -V`

Display version information and exit.

- `--view-protocol`

Every `SELECT` statement is wrapped inside a view. This option was added in MySQL 5.0.19.

## 4.2. `mysql-test-run.pl` — Run MySQL Test Suite

The `mysql-test-run.pl` Perl script is the main application used to run the test suite for MySQL 5.1 and up. It invokes `mysqltest` to run individual test cases. (Prior to MySQL 5.1, `mysql-test-run` can be used instead.)

Invoke `mysql-test-run.pl` in the `mysql-test` directory like this:

```
shell> mysql-test-run.pl [options] [test_name] ...
```

Each `test_name` argument names a test case. The test case file that corresponds to the test name is `t/test_name.test`.

For each `test_name` argument, `mysql-test-run.pl` runs the named test case. With no `test_name` arguments, `mysql-test-run.pl` runs all `.test` files in the `t` subdirectory.

To run a family of test cases for which the names share a common prefix, use the `--do-tests=prefix` option. For example, `--do-tests=rpl` runs the replication tests (test cases that have names beginning with `rpl`).

`mysql-test-run.pl` defines several environment variables. Some of them are listed in the following table.

Variable	Meaning
<code>MYSQL_TEST</code>	Pathname to <code>mysqltest</code> binary
<code>MYSQLTEST_VARDIR</code>	Pathname to the <code>var</code> directory that is used for logs, temporary files, and

	so forth
MASTER_MYPORT	???
MASTER_MYSOCK	???

Tests sometimes rely on certain environment variables being defined. For example, certain tests assume that `MYSQL_TEST` is defined so that `mysqltest` can invoke itself with `exec $MYSQL_TEST`.

`mysql-test-run.pl` supports the options in the following list. An argument of `--` tells `mysql-test-run.pl` not to process any following arguments as options. (A description of differences between the options supported by `mysql-test-run.pl` and `mysql-test-run` appears following the list.)

- `--help, -h`  
Display a help message and exit.
- `--bench`  
Run the benchmark suite.
- `--benchdir=path`  
The directory where the benchmark suite is located. The default path is `../..mysql-bench`.
- `--big-test`  
Pass the `--big-test` option to `mysqltest`.
- `--check-testcases`  
Check test cases for side effects.
- `--client-ddd`  
Start `mysqltest` in the `ddd` debugger.
- `--client-debugger`  
Start `mysqltest` in the named debugger.
- `--client-gdb`  
Start `mysqltest` in the `gdb` debugger.
- `--comment=str`  
Write `str` to the output.
- `--compress`  
Compress all information sent between the client and the server if both support compression.
- `--cursor-protocol`  
Pass the `--cursor-protocol` option to `mysqltest` (implies `--ps-protocol`).
- `--ddd`

Start `mysqld` in the `ddd` debugger.

- `--debug`

Dump trace output for all clients and servers.

- `--debugger`

Start `mysqld` the named debugger.

- `--do-test=prefix`

Run all test cases having a name that begins with the given `prefix` value. This option provides a convenient way to run a family of similarly named tests.

- `--embedded-server`

Use a version of `mysqltest` built with the embedded server.

- `--extern`

Use an already running server.

Note: If a test case has an `.opt` file that requires the server to be restarted with specific options, the file will not be used. The test case likely will fail as a result.

- `--fast`

Do not clean up from earlier test runs.

- `--force`

Normally, `mysql-test-run.pl` exits if a test case fails. `--force` causes execution to continue regardless of test case failure.

- `--gcov`

Run tests with the `gcov` test coverage tool.

- `--gdb`

Start `mysqld` in the `gdb` debugger.

- `--gprof`

Run tests with the `gprof` profiling tool.

- `--im-mysqld1-port`

TCP/IP port number to use for the first `mysqld`, controlled by Instance Manager.

- `--im-mysqld2-port`

TCP/IP port number to use for the second `mysqld`, controlled by Instance Manager.

- `--im-port`

TCP/IP port number to use for `mysqld`, controlled by Instance Manager.

- `--log-warnings`

Pass the `--log-warnings` option to `mysqld`.

- `--manual-debug`

Use a server that has already been started by the user in a debugger.

- `--manual-gdb`

Use a server that has already been started by the user in the `gdb` debugger.

- `--master-binary=path`

Specify the path of the `mysqld` binary to use for master servers.

- `--master_port=port_num`

Specify the TCP/IP port number for the first master server to use. Observe that the option name has an underscore and not a dash.

- `--mysqld=str`

Extra options to pass to `mysqld`.

- `--ndb-connectstring=str`

Pass `--ndb-connectstring=str` to the master MySQL server. This option also prevents `mysql-test-run.pl` from starting a cluster. It is assumed that there is already a cluster running to which the server can connect with the given connectstring.

- `--ndb-connectstring-slave=str`

Pass `--ndb-connectstring=str` to slave MySQL servers. This option also prevents `mysql-test-run.pl` from starting a cluster. It is assumed that there is already a cluster running to which the server can connect with the given connectstring.

- `--ndb-extra-test`

Unknown.

- `--ndbcluster-port=port_num, --ndbcluster_port=port_num`

Specify the TCP/IP port number that NDB Cluster should use.

- `--ndbcluster-port-slave=port_num`

Specify the TCP/IP port number that the slave NDB Cluster should use.

- `--netware`

Run `mysqld` with options needed on NetWare.

- `--notimer`

Cause `mysqltest` not to generate a timing file.

- `--ps-protocol`

Pass the `--ps-protocol` option to `mysqltest`.

- `--record`  
Pass the `--record` option to `mysqltest`. This option requires a specific test case to be named on the command line.
- `--reorder`  
Reorder tests to minimize the number of server restarts needed.
- `--script-debug`  
Enable debug output for `mysql-test-run.pl` itself.
- `--skip-im`  
Do not start Instance Manager; skip Instance Manager test cases.
- `--skip-master-binlog`  
Do not enable master server binary logging.
- `--skip-ndbcluster`, `--skip-ndb`  
Do not start NDB Cluster; skip Cluster test cases.
- `--skip-ndbcluster-slave`, `--skip-ndb-slave`  
Do not start an NDB Cluster slave.
- `--skip-rpl`  
Skip replication test cases.
- `--skip-slave-binlog`  
Do not enable master server binary logging.
- `--skip-ssl`  
Do not start `mysqld` with support for SSL connections.
- `--skip-test=regex`  
Specify a regular expression to be applied to test case names. Cases with names that match the expression are skipped. tests to skip.
- `--skip-*`  
`--skip-*` options not otherwise recognized by `mysql-test-run.pl` are passed to the master server.
- `--slave-binary=path`  
Specify the path of the `mysqld` binary to use for slave servers.
- `--slave_port=port_num`  
Specify the TCP/IP port number for the first master server to use. Observe that the option name has an underscore and not a dash.

- `--sleep=N`

Pass `--sleep=N` to `mysqltest`.

- `--small-bench`

Run the benchmarks with the `--small-tests` and `--small-tables` options.

- `--socket=file_name`

For connections to `localhost`, the Unix socket file to use, or, on Windows, the name of the named pipe to use.

- `--sp-protocol`

Pass the `--sp-protocol` option to `mysqltest`.

- `--ssl`

If `mysql-test-run.pl` is started with the `--ssl` option, it sets up a secure connection for all test cases. In this case, if `mysqld` does not support SSL, `mysql-test-run.pl` exits with an error message: `Couldn't find support for SSL`

- `--start-and-exit`

Initialize and start servers with the startup settings for the specified test case or cases, if any, and then exit.

- `--start-dirty`

Start servers (without initialization) for the specified test case or cases, if any, and then exit. You can then manually run the test cases.

- `--start-from=test_name`

`mysql-test-run.pl` sorts the list of names of the test cases to be run, and then begins with `test_name`.

- `--strace-client`

Create `strace` output for `mysqltest`.

- `--stress`

Run the stress test. The other `--stress-xxx` options apply in this case.

- `--stress-init-file=file_name`

`file_name` is the location of the file that contains the list of tests. The default file is `stress_init.txt` in the test suite directory.

- `--stress-loop-count=N`

In sequential stress-test mode, the number of loops to execute before exiting.

- `--stress-mode=mode`

This option indicates the test order in stress-test mode. The `mode` value is either `random` to select tests in random order or `seq` to run tests in each thread in the order specified in the test list file. The default mode is `random`.

- `--stress-suite=suite_name`

The name of the test suite to use for stress testing. The default suite name is `main` (the regular test suite located in the `mysql-test` directory).
- `--stress-test-count=N`

For stress testing, the number of tests to execute before exiting.
- `--stress-test-duration=N`

For stress testing, the duration of stress testing in seconds.
- `--stress-test-file=file_name`

The file that contains the list of tests to use in stress testing. The tests should be named without the `.test` extension. The default file is `stress_tests.txt` in the test suite directory.
- `--stress-threads=N`

The number of threads to use in stress testing. The default is 5.
- `--suite=suite_name`

Run the named test suite. The default name is `main` (the regular test suite located in the `mysql-test` directory).
- `--suite-timeout=minutes`

Specify the maximum test suite runtime.
- `--testcase-timeout`

Specify the maximum test case runtime.
- `--timer`

Cause `mysqltest` to generate a timing file. The default file is named `./var/log/timer`.
- `--tmpdir=path`

The directory where temporary file are stored. The default location is `./var/tmp`.
- `--unified-diff, --udiff`

Use unified diff format when presenting differences between expected and actual test case results.
- `--use-old-data`

Do not install the test databases. (Use existing ones.)
- `--user-test=val`

Unused.
- `--user=user_name`

The MySQL username to use when connecting to the server.
- `--valgrind`



Run `mysqltest` and `mysqld` with `valgrind`.

- `--valgrind-all`

Like `--valgrind`, but passes the `--verbose` and `--show-reachable` options to `valgrind`.

- `--valgrind-mysqltest`

Run `mysqltest` with `valgrind`.

- `--valgrind-mysqltest-all`

Like `--valgrind-mysqltest`, but passes the `--verbose` and `--show-reachable` options to `valgrind`.

- `--valgrind-options=str`

Extra options to pass to `valgrind`.

- `--valgrind-path=path`

Specify the pathname to the `valgrind` executable.

- `--vardir=path`

Specify the path where files generated during the test run are stored. The default location is `./var`.

- `--view-protocol`

Pass the `--view-protocol` option to `mysqltest`.

- `--wait-timeout=N`

Unused?

- `--warnings`

This option is a synonym for `--log-warnings`.

- `--with-ndbcluster`

Use NDB Cluster and enable test cases that require it.

- `--with-ndbcluster-all`

Use NDB Cluster in all tests.

- `--with-ndbcluster-only`

Run only test cases that have `ndb` in their name.

- `--with-ndbcluster-slave`

Unknown.

- `--with-openssl`

This option is a synonym for `--ssl`.

**Note**

`mysql-test-run` supports the following options not supported by `mysql-test-run.pl`: `--local`, `--local-master`, `--ndb-verbose`, `-ndb_mgm-extra-opts`, `--ndb_mgmd-extra-opts`, `--ndbd-extra-opts`, `-old-master`, `--purify`, `--use-old-data`, `--valgrind-mysqld-test-all`.

Conversely, `mysql-test-run.pl` supports the following options not supported by `mysql-test-run`: `--benchdir`, `--check-testcases`, `--client-ddd`, `-client-debugger`, `--cursor-protocol`, `--debugger`, `-im-mysqld1-port`, `--im-mysqld2-port`, `--im-port`, `--manual-debug`, `-netware`, `--notimer`, `--reorder`, `--script-debug`, `--skip-im`, `-skip-ssl`, `--sp-protocol`, `--start-dirty`, `--suite`, `--suite-timeout`, `--testcase-timeout`, `--udiff`, `--unified-diff`, `--valgrind-path`, `-vardir`, `--view-protocol`.

## 4.3. `mysql-test-run` — Run MySQL Test Suite

The `mysql-test-run` shell script is the main application used to run the test suite before MySQL 5.1. It invokes `mysqltest` to run individual test cases. (`mysql-test-run.pl` is preferred as of 5.1.)

`mysql-test-run` is a shell script, so it does not run on Windows. The replacement script (`mysql-test-run.pl`) is written in Perl and therefore has better cross-platform portability.

Invoke `mysql-test-run` in the `mysql-test` directory like this:

```
shell> mysql-test-run [options] [test_name] ...
```

Each `test_name` argument names a test case. The test case file that corresponds to the test name is `t/test_name.test`.

For each `test_name` argument, `mysql-test-run` runs the named test case. With no `test_name` arguments, `mysql-test-run` runs all `.test` files in the `t` subdirectory.

To run a family of test cases for which the names share a common prefix, use the `--do-tests=prefix` option. For example, `--do-tests=rpl` runs the replication tests (test cases that have names beginning with `rpl`).

`mysql-test-run` defines several environment variables. Some of them are listed in the following table.

Variable	Meaning
<code>MYSQL_TEST</code>	Pathname to <code>mysqltest</code> binary
<code>MYSQLEST_VARDIR</code>	Pathname to the <code>var</code> directory that is used for logs, temporary files, and so forth
<code>MASTER_MYPORT</code>	Master server TCP/IP port number
<code>MASTER_MYSOCK</code>	Master server Unix socket file

Tests sometimes rely on certain environment variables being defined. For example, certain tests assume that `MYSQL_TEST` is defined so that `mysqltest` can invoke itself with `exec $MYSQL_TEST`.

`mysql-test-run` supports the options in the following list. An argument of `--` tells `mysql-test-run` not to process any following arguments as options. (A description of differences between

the options supported by `mysql-test-run` and `mysql-test-run.pl` appears in [Section 4.2](#), “`mysql-test-run.pl` — Run MySQL Test Suite”.)

- `--bench`  
Run the benchmark suite.
- `--big-test`  
Pass the `--big-test` option to `mysqltest`.
- `--client-gdb`  
Start `mysqltest` in the `gdb` debugger.
- `--comment=str`  
Write `str` to the output.
- `--compress`  
Compress all information sent between the client and the server if both support compression.
- `--ddd`  
Start `mysqld` in the `ddd` debugger.
- `--debug`  
Dump trace output for all clients and servers.
- `--do-test=prefix`  
Run all test cases having a name that begins with the given `prefix` value. This option provides a convenient way to run a family of similarly named tests.
- `--embedded-server`  
Use a version of `mysqltest` built with the embedded server.
- `--extern`  
Use an already running server.  
  
Note: If a test case has an `.opt` file that requires the server to be restarted with specific options, the file will not be used. The test case likely will fail as a result.
- `--fast`  
Do not clean up from earlier test runs.
- `--force`  
Normally, `mysql-test-run` exits if a test case fails. `--force` causes execution to continue regardless of test case failure.
- `--gcov`  
Run tests with the `gcov` test coverage tool.

- `--gdb`  
Start `mysqld` in the `gdb` debugger.
- `--gprof`  
Run tests with the `gprof` profiling tool.
- `--local`  
Do not use an already running server. `mysql-run-test` starts a server and tells `mysqltest` to use it. This is the default as of MySQL 4.1.
- `--local-master`  
Unknown. (Assume the master server is already running?)
- `--log-warnings`  
Pass the `--log-warnings` option to `mysqld`.
- `--manual-gdb`  
Use a server that has already been started by the user in the `gdb` debugger.
- `--master-binary=path`  
Specify the path of the `mysqld` binary to use for master servers.
- `--master_port=port_num`  
Specify the TCP/IP port number for the first master server to use. Observe that the option name has an underscore and not a dash.
- `--mysqld=str`  
Extra options to pass to `mysqld`.
- `--ndb-connectstring=str`  
Pass `--ndb-connectstring=str` to the master MySQL server. This option also prevents `mysql-test-run` from starting a cluster. It is assumed that there is already a cluster running to which the server can connect with the given connectstring.
- `--ndb-connectstring-slave=str`  
Pass `--ndb-connectstring=str` to slave MySQL servers. This option also prevents `mysql-test-run` from starting a cluster. It is assumed that there is already a cluster running to which the server can connect with the given connectstring.
- `--ndb-extra-test`  
Unknown.
- `--ndb-verbose`  
Unknown.
- `--ndb_mgm-extra-opts=str`

Extra options to pass to `ndb_mgm`. Observe that the option name contains an underscore.

- `--ndb_mgmd-extra-opts=str`

Extra options to pass to `ndb_mgmd`. Observe that the option name contains an underscore.

- `--ndbcluster-port=port_num, --ndbcluster_port=port_num`

Specify the TCP/IP port number that NDB Cluster should use.

- `--ndbcluster-port-slave=port_num`

Specify the TCP/IP port number that the slave NDB Cluster should use.

- `--ndbd-extra-opts=str`

Extra options to pass to `ndbd`.

- `--old-master`

When `mysql-test-run` is run against an old (4.0) server, this option prevents certain arguments from being passed to the server.

- `--ps-protocol`

Pass the `--ps-protocol` option to `mysqltest`.

- `--purify`

Use the Purify memory-leak detector.

- `--record`

Pass the `--record` option to `mysqltest`. This option requires a specific test case to be named on the command line.

- `--skip-master-binlog`

Do not enable master server binary logging.

- `--skip-ndbcluster, --skip-ndb`

Do not start NDB Cluster; skip Cluster test cases.

- `--skip-ndbcluster-slave, --skip-ndb-slave`

Do not start an NDB Cluster slave.

- `--skip-rpl`

Skip replication test cases.

- `--skip-slave-binlog`

Do not enable master server binary logging.

- `--skip-test=regex`

Specify a regular expression to be applied to test case names. Cases with names that match the ex-

pression are skipped. tests to skip.

- `--skip-*`  
`--skip-*` options not otherwise recognized by `mysql-test-run` are passed to the master server.
- `--slave-binary=path`  
Specify the path of the `mysqld` binary to use for slave servers.
- `--slave_port=port_num`  
Specify the TCP/IP port number for the first master server to use. Observe that the option name has an underscore and not a dash.
- `--sleep=N`  
Pass `--sleep=N` to `mysqltest`.
- `--small-bench`  
Run the benchmarks with the `--small-tests` and `--small-tables` options.
- `--socket=file_name`  
For connections to `localhost`, the Unix socket file to use, or, on Windows, the name of the named pipe to use.
- `--start-and-exit`  
Initialize and start servers with the startup settings for the specified test case or cases, if any, and then exit.
- `--start-from=test_name`  
`mysql-test-run` sorts the list of names of the test cases to be run, and then begins with `test_name`.
- `--strace-client`  
Create `strace` output for `mysqltest`.
- `--stress`  
Run the stress test. The other `--stress-xxx` options apply in this case.
- `--stress-init-file=file_name`  
`file_name` is the location of the file that contains the list of tests. The default file is `stress_init.txt` in the test suite directory.
- `--stress-loop-count=N`  
In sequential stress-test mode, the number of loops to execute before exiting.
- `--stress-mode=mode`  
This option indicates the test order in stress-test mode. The `mode` value is either `random` to select

tests in random order or `seq` to run tests in each thread in the order specified in the test list file. The default mode is `random`.

- `--stress-suite=suite_name`

The name of the test suite to use for stress testing. The default suite name is `main` (the regular test suite located in the `mysql-test` directory).

- `--stress-test-count=N`

For stress testing, the number of tests to execute before exiting.

- `--stress-test-duration=N`

For stress testing, the duration of stress testing in seconds.

- `--stress-test-file=file_name`

The file that contains the list of tests to use in stress testing. The tests should be named without the `.test` extension. The default file is `stress_tests.txt` in the test suite directory.

- `--stress-threads=N`

The number of threads to use in stress testing. The default is 5.

- `--timer`

Cause `mysqltest` to generate a timing file. The default file is named `./var/log/timer`.

- `--tmpdir=path`

The directory where temporary file are stored. The default location is `./var/tmp`.

- `--use-old-data`

Do not install the test databases. (Use existing ones.)

- `--user-test=val`

Unused.

- `--user=user_name`

The MySQL username to use when connecting to the server.

- `--valgrind`

Run `mysqltest` and `mysqld` with `valgrind`.

- `--valgrind-all`

Like `--valgrind`, but passes the `--verbose` and `--show-reachable` options to `valgrind`.

- `--valgrind-mysqltest`

Run `mysqltest` with `valgrind`.

- `--valgrind-mysqltest-all`

Like `--valgrind-mysqldtest`, but passes the `--verbose` and `--show-reachable` options to `valgrind`.

- `--valgrind-options=str`

Extra options to pass to `valgrind`.

- `--wait-timeout=N`

Unused?

- `--warnings`

This option is a synonym for `--log-warnings`.

- `--with-ndbcluster`

Use NDB Cluster and enable test cases that require it.

- `--with-ndbcluster-all`

Use NDB Cluster in all tests.

- `--with-ndbcluster-only`

Run only test cases that have `ndb` in their name.

- `--with-ndbcluster-slave`

Unknown.

- `--with-openssl`

If `mysql-test-run` is started with the `--ssl` option, it sets up a secure connection for all test cases. In this case, if `mysqld` does not support SSL, `mysql-test-run` exits with an error message: `Couldn't find support for SSL`

## 4.4. `mysql-stress-test.pl` — Server Stress Test Program

The `mysql-stress-test.pl` Perl script performs stress-testing of the MySQL server. (MySQL 5.0 and up only)

`mysql-stress-test.pl` requires a version of Perl that has been built with threads support.

Invoke `mysql-stress-test.pl` like this:

```
shell> mysql-stress-test.pl [options]
```

`mysql-stress-test.pl` supports the following options:

- `--help`

Display a help message and exit.



- `--abort-on-error`

Unknown.

- `--check-tests-file`

Periodically check the file that lists the tests to be run. If it has been modified, reread the file. This can be useful if you update the list of tests to be run during a stress test.

- `--cleanup`

Force cleanup of the working directory.

- `--log-error-details`

Log error details in the global error log file.

- `--loop-count=N`

In sequential test mode, the number of loops to execute before exiting.

- `--mysqltest=path`

The pathname to the `mysqltest` program.

- `--server-database=db_name`

The database to use for the tests.

- `--server-host=host_name`

The hostname of the local host to use for making a TCP/IP connection to the local server. By default, the connection is made to `localhost` using a Unix socket file.

- `--server-logs-dir=path`

This option is required. `path` is the directory where all client session logs will be stored. Usually this is the shared directory that is associated with the server used for testing.

- `--server-password=password`

The password to use when connecting to the server.

- `--server-port=port_num`

The TCP/IP port number to use for connecting to the server. The default is 3306.

- `--server-socket=file_name`

For connections to `localhost`, the Unix socket file to use, or, on Windows, the name of the named pipe to use. The default is `/tmp/mysql.sock`.

- `--server-user=user_name`

The MySQL username to use when connecting to the server. The default is `root`.

- `--sleep-time=N`

The delay in seconds between test executions.

- `--stress-basedir=path`

This option is required. *path* is the working directory for the test run. It is used as the temporary location for result tracking during testing.

- `--stress-datadir=path`

The directory of data files to be used during testing. The default location is the `data` directory under the location given by the `--stress-suite-basedir` option.

- `--stress-init-file[=path]`

*file\_name* is the location of the file that contains the list of tests. If missing, the default file is `stress_init.txt` in the test suite directory.

- `--stress-mode=mode`

This option indicates the test order in stress-test mode. The *mode* value is either `random` to select tests in random order or `seq` to run tests in each thread in the order specified in the test list file. The default mode is `random`.

- `--stress-suite-basedir=path`

This option is required. *path* is the directory that has the `t` and `r` subdirectories containing the test case and result files. This directory is also the default location of the `stress-test.txt` file that contains the list of tests. (A different location can be specified with the `--stress-tests-file` option.)

- `--stress-tests-file[=file_name]`

Use this option to run the stress tests. *file\_name* is the location of the file that contains the list of tests. If *file\_name* is omitted, the default file is `stress-test.txt` in the stress suite directory. (See `--stress-suite-basedir`.)

- `--suite=suite_name`

Run the named test suite. The default name is `main` (the regular test suite located in the `mysql-test` directory).

- `--test-count=N`

The number of tests to execute before exiting.

- `--test-duration=N`

The duration of stress testing in seconds.

- `--test-suffix=str`

Unknown.

- `--threads=N`

The number of threads. The default is 1.

- `--verbose`

Verbose mode. Print more information about what the program does.

---

# Chapter 5. `mysqltest` Language Reference

This chapter describes the test language implemented by `mysqltest`. The language allows input to contain a mix of comments, commands executed by `mysqltest` itself, and SQL statements that `mysqltest` sends to a MySQL server for execution.

## Terminology notes:

- A “command” is an input test that `mysqltest` recognizes and executes itself. A “statement” is an SQL statement or query that `mysqltest` sends to the MySQL server to be executed.
- When `mysqltest` starts, it opens a connection named `default` to the MySQL server, using any connection parameters specified by the command options. (For a local server, the default username is `root`. For an external server, the default username is `test` or the user specified with the `-user` option.) You can use the `connect` command to open other connections, the `connection` command to switch between connections, and the `disconnect` command to close connections. However, the capability for switching connections means that the connection named `default` need not be the connection in use at a given time. To avoid ambiguity, this document avoids the term “default connection.” It uses the term “current connection” to mean “the connection currently in use,” which might be different from “the connection named `default`.”

## 5.1. `mysqltest` Input Conventions

`mysqltest` reads input lines and processes them as follows:

- “End of line” means a newline (linefeed) character. A carriage return/linefeed (CRLF) pair also is allowable as a line terminator (the carriage return is ignored). Carriage return by itself is *not* allowed as a line terminator.
- A line that begins with `#` as the first non-whitespace content is treated as a comment that extends to the end of the line and is ignored. Example:

```
# this is a comment
```

- A line that begins with `--` as the first non-whitespace content also is treated as a comment that extends to the end of the line. However, unlike `#` comments, if the first word of the comment is a valid `mysqltest` command, `mysqltest` executes the line from that word to the end of the line as a command.

`mysqltest` interprets the following lines as comments because the first word is not a `mysqltest` command:

```
-- this is a comment
-- clean up from previous test runs
```

`mysqltest` interprets the following lines as commands and executes them because the first word is a `mysqltest` command:

```
--disconnect conn1
-- error 1050
```

The `--` syntax is useful for writing commands that contain embedded instances of the command delimiter:

```
-- echo write this text; it goes to the result file
```

- Other input is taken as normal command input. The command extends to the next occurrence of the command delimiter, which is semicolon (‘;’) by default. The delimiter can be changed with the `delimiter` command.

If `mysqltest` recognizes the first word of the delimiter-terminated command, `mysqltest` executes the command itself. Otherwise, `mysqltest` assumes that the command is an SQL statement and sends it to the MySQL server to be executed.

Because the command extends to the delimiter, a given input line can contain multiple commands, and a given command can span multiple lines. The ability to write multiple-line statements is useful for making long statements more readable, such as a `create table` statement for a table that has many columns.

After `mysqltest` reads a command up to a delimiter and executes it, input reading restarts following the delimiter and any remaining input on the line that contains the delimiter is treated as though it begins on a new line. Consider the following two input lines:

```
echo issue a select statement; select 1; echo done
issuing the select statement;
```

That input contains two commands and one SQL statement:

```
echo issue a select statement
select 1
echo done issuing the select statement
```

Similarly, ‘#’ comments or ‘--’ comments can begin on a command line following a delimiter:

```
select 'hello'; # select a string value
select 'hello'; -- echo that was a select statement
```

On a multiple-line command, ‘#’ or ‘--’ at the beginning of the second or following lines is not special. Thus, the second and third lines of the following variable-assignment command are not taken as comments. Instead, the variable `$a` is set to a value that contains two linefeed characters:

```
let $a = This is a variable
# assignment that sets a variable
-- to a multiple-line value;
```

Note that ‘--’ comments and normal commands have complementary properties with regard to how `mysqltest` reads them:

- A ‘--’ comment is terminated by a newline, regardless of how many delimiters it contains.
- A normal command (without ‘--’) is terminated by the delimiter (semicolon), no matter how many newlines it contains.

`mysqltest` commands can be written either as comments (with a leading ‘--’) or as normal command input (no leading ‘--’). Use the command delimiter only in the latter case. Thus, these two lines are equivalent:

```
--sleep 2
sleep 2;
```

The equivalence is true even for the `delimiter` command. For example, to set the delimiter to `‘//’`, either of these commands work:

```
--delimiter //
delimiter //;
```

To set the delimiter back to `‘;’`, use either of these commands:

```
--delimiter ;
delimiter ;//
```

The input language has certain ambiguities. For example, if you write the following line, intending it as a comment that indicates where test 43 ends, it will not work:

```
-- End of test 43
```

The “comment” is not treated as such because `end` is a valid `mysqltest` command. Thus, although it is *possible* to write a non-command comment that begins with `‘--’`, it is better to use `‘#’` instead. Writing comments with `‘#’` also has less potential to cause problems in the future. For example, `mysqltest` interprets the line `--switch to conn1` as a comment currently, but if `mysqltest` is extended in the future to add a `switch` command, that line will be treated as a command instead. If you use `‘#’` for all comments, this problem will not occur.

Another ambiguity occurs because a non-comment line can contain either a `mysqltest` command or an SQL statement. This has a couple of implications:

- No `mysqltest` command should be the same as any keyword that can begin an SQL statement.
- Should extensions to SQL be implemented in the future, it's possible that a new SQL keyword could be impossible for `mysqltest` to recognize as such if that keyword is already used as a `mysqltest` command.

## 5.2. mysqltest Commands

`mysqltest` supports the commands described in this section. Command names are not case sensitive.

Some examples of command use are given, but you can find many more by searching the test case files in the `mysql-test/t` directory.

- `character_set charset_name`

Set the default character set to `charset_name`. Initially, the character set is `latin1`.

```
character_set utf8;
--character_set sjis
```

- `connect (name, host_name, user_name, password, db_name [,port_num [,socket [,options]]])`

Open a connection to the server and make the connection the current connection. (Syntax oddities: There must be whitespace between `connect` and the opening parenthesis, and no whitespace after the opening parenthesis.)

The arguments to `connect` are:

- `name` is the name for the connection (for use with the `connection`, `disconnect`, and `dirty_close` commands). This name must not already be in use by an open connection.
- `host_name` indicates the host where the server is running.
- `user_name` and `password` are the username and password of the MySQL account to use.
- `db_name` is the default database to use. As a special case, `*NO-ONE*` means that no default database should be selected. You can also leave `db_name` blank to select no database.
- `port_num`, if given, is the TCP/IP port number to use for the connection. This parameter can be given by using a variable.
- `socket`, if given, is the socket file to use for connections to `localhost`. This parameter can be given by using a variable.
- `options` can be one or more of the words `SSL` and `COMPRESS`, separated by spaces. These specify the use of SSL and the compressed client/server protocol, respectively.

To omit an argument, just leave it blank. For an omitted argument, `mysqltest` uses an empty string for the first five arguments and the `options` argument. For omitted port or socket options, `mysqltest` uses the default port or socket.

```
connect (conn1,localhost,root,,);
connect (conn2,localhost,root,mypass,test);
connect (conn1,127.0.0.1,root,,test,$MASTER_MYPORT);
```

The last example assumes that the `$MASTER_MYPORT` variable has already been set (perhaps as an environment variable).

If a connection attempt fails initially, `mysqltest` retries five times if the abort-on-error setting is enabled.

- `connection connection_name`

Select `connection_name` as the current connection. To select the connection that `mysqltest` opens when it starts, use the name `default`.

```
connection master;
connection conn2;
connection default;
```

- `dec $var_name`

Decrement a numeric variable. If the variable does not have a numeric value, the result is undefined.

```
dec $count;
dec $2;
```

- `delimiter str`

Set the command delimiter to `str`, which may consist of 1 to 15 characters. The default delimiter is the semicolon character (`';`).

```
delimiter //;
--delimiter stop
```

- `dirty_close connection_name`

Close the named connection. This is like `disconnect` except that it calls `vio_delete()` before it closes the connection. If the connection is the current connection, you should use the `connection` command to switch to a different connection before executing further SQL statements.

- `disable_abort_on_error, enable_abort_on_error`

Disable or enable abort-on-error behavior. This setting is enabled by default. With this setting enabled, `mysqltest` aborts the test when a statement sent to the server results in an unexpected error, and does not generate the `.reject` file. For discussion of reasons why it can be useful to disable this behavior, see [Section 5.5, “Error Handling”](#).

```
--disable_abort_on_error
--enable_abort_on_error
```

- `disable_info, enable_info`

Disable or enable additional information about SQL statement results. This setting is disabled by default. With this setting enabled, `mysqltest` displays the affected-rows count and the output from the `mysql_info()` C API function. The “affected-rows” value is “rows selected” for statements such as `SELECT` and “rows modified” for statements that change data.

```
--disable_info
--enable_info
```

- `disable_metadata, enable_metadata`

Disable or enable query metadata display. This setting is disabled by default. With this setting enabled, `mysqltest` adds query metadata to the result. This information consists of the values corresponding to the members of the `MYSQL_FIELD` C API data structure, for each column of the result.

```
--disable_metadata
--enable_metadata
```

- `disable_parsing, enable_parsing`

Disable or enable query parsing. This setting is enabled by default. When disabled, `mysqltest` ignores everything until `enable_parsing`.

```
--disable_parsing
--enable_parsing
```

- `disable_ps_protocol, enable_ps_protocol`

Disable or enable prepared-statement protocol. This setting is disabled by default unless the `-ps-protocol` option is given.

```
--disable_ps_protocol
--enable_ps_protocol
```

- `disable_ps_warnings, enable_ps_warnings`

Disable or enable prepared-statement warnings. This setting is enabled by default.

```
--disable_ps_warnings
--enable_ps_warnings
```

- `disable_query_log`, `enable_query_log`

Disable or enable query logging. This setting is enabled by default. With this setting enabled, `mysqltest` echoes input SQL statements to the test result.

One reason to disable query logging is to reduce the amount of test output produced, which also makes comparison of actual and expected results more efficient.

```
--disable_query_log
--enable_query_log
```

- `disable_reconnect`, `enable_reconnect`

Disable or enable automatic reconnect for dropped connections. (The default depends on the client library version.) This command applies to connections made afterward.

```
--disable_reconnect
--enable_reconnect
```

- `disable_result_log`, `enable_result_log`

Disable or enable the result log. This setting is enabled by default. With this setting enabled, `mysqltest` displays query results (and results from commands such as `echo` and `exec`).

```
--disable_result_log
--enable_result_log
```

- `disable_rpl_parse`, `enable_rpl_parse`

Disable or enable parsing of statements to determine whether they go to the master or slave. (MySQL 4.0 and up only.) The default is whatever the default is for the C API library.

```
--disable_rpl_parse
--enable_rpl_parse
```

- `disable_warnings`, `enable_warnings`

Disable or enable warnings. This setting is enabled by default. With this setting enabled, `mysqltest` uses `SHOW WARNINGS` to display any warnings produced by SQL statements.

```
--disable_warnings
--enable_warnings
```

- `disconnect connection_name`

Close the named connection. If the connection is the current connection, you should use the `connection` command to switch to a different connection before executing further SQL statements.

```
disconnect conn2;
disconnect slave;
```

- `echo text`

Echo the text to the test result. References to variables within the text are replaced with the corresponding values.

```
--echo "Another sql_mode test"
echo "should return only 1 row";
```



- `end`

End an `if` or `while` block. If there is no such block open, `mysqltest` exits with an error. See [Section 5.4, “mysqltest Flow Control Constructs”](#), for information on flow-control constructs.

`mysqltest` considers `}` and `end` the same: Both end the current block.

- `end_timer`

Stop the timer. By default, the timer does not stop until just before `mysqltest` exits.

- `error error_code [, error_code] ...`

Specify one or more comma-separated error values that the next command is expected to return. Each `error_code` value is a MySQL-specific error number or a SQLSTATE value. (These are the kinds of values returned by the `mysql_errno()` and `mysql_sqlstate()` C API functions, respectively.)

If you specify a SQLSTATE value, it should begin with an `S` to enable `mysqltest` to distinguish it from a MySQL error number. For example, the error number 1050 and the SQLSTATE value `42S01` are equivalent, so the following commands specify the same expected error:

```
--error 1050
--error S42S01
```

It is also possible to use the symbolic error name from `mysqld_error.h`:

```
--error ER_TABLE_EXISTS_ERROR
```

If a statement fails with an error that has not been specified as expected by means of a `error` command, `mysqltest` aborts and reports the error message returned by the MySQL server.

If a statement fails with an error that has been specified as expected by means of a `error` command, `mysqltest` does not abort. Instead, it continues and writes a message to the result output.

- If an `error` command is given with a single error value and the statement fails with that error, `mysqltest` reports the error message returned by the MySQL server.

Input:

```
--error S42S02
drop table t;
```

`mysqltest` reports:

```
ERROR 42S02: Unknown table 't'
```

- If an `error` command is given with multiple error values and the statement fails with that error, `mysqltest` reports a generic message. (This is true even if the error values are all the same, a fact that can be used if you want a message that does not contain varying information such as table names.)

Input:

```
--error S41S01,S42S02
drop table t;
```

`mysqltest` reports:

```
Got one of the listed errors
```

An error value of 0 or `S00000` means “no error,” so using either for an `error` command is the same as saying explicitly, “no error is expected, the statement must succeed.”

To indicate that you expect success or a given error or errors, specify 0 or `S00000` first in the error list. If you put the no-error value later in the list, the test will abort if the statement is successful. That is, these two commands have different effects:

```
--error 0,1051
--error 1051,0
```

You can use `error` to specify shell status values for testing the value of shell commands executed via the `exec` command. This does not apply to `system`, for which the command status is ignored.

- `eval statement`

Evaluate the statement by replacing references to variables within the text with the corresponding values. Then send the resulting statement to the server to be executed. Use ‘\’ to specify a literal ‘\$’ character.

The advantage of using `eval statement` versus just `statement` is that `eval` provides variable expansion.

```
eval use $DB;
eval change master to master_port=$SLAVE_MYPORT;
eval prepare stmt1 from "$my_stmt";
```

- `eval_result`

Unknown.

- `exec command [arg] ...`

Execute the shell command using the `popen()` library call. References to variables within the command are replaced with the corresponding values. Use ‘\’ to specify a literal ‘\$’ character.

On Cygwin, the command is executed from `cmd.exe`, so commands such as `rm` cannot be executed with `exec`. Use `system` instead.

```
--exec $MYSQL_DUMP --xml --skip-create test
--exec rm $MYSQLTEST_VARDIR/tmp/t1
exec $MYSQL_SHOW test -v -v;
```

- `exit`

Terminate the test case. This is considered a “normal termination.” That is, using `exit` does not result in evaluation of the test case as having failed.

- `horizontal_results`

Set the default query result display format to horizontal. Initially, the default is to display results horizontally.

```
--horizontal_results
```

- `if (expr)`

Begin an `if` block, which continues until an `end` line. `mysqltest` executes the block if the expression is true. There is no provision for `else` with `if`. See [Section 5.4, “mysqltest Flow Control Constructs”](#), for further information about `if` statements.

```
let $counter=0;
if ($counter)
{
  echo Counter is greater than 0, (counter=0);
}
if (!$counter)
{
  echo Counter is not 0, (counter=0);
}
```

- `inc $var_name`

Increment a numeric variable. If the variable does not have a numeric value, the result is undefined.

```
inc $i;
inc $3;
```

- `let $var_name = value`

Assign a value to a variable. The variable name cannot contain whitespace or the '=' character. `mysqltest` aborts with an error if the value is erroneous.

As of MySQL 5.0.26/5.1.12, references to variables within `value` are replaced with their corresponding values.

If the `let` command is specified as a normal command (that is, not beginning with '--'), `value` includes everything up to the command delimiter, and thus can span multiple lines.

```
--let $i = 0
let $count = 10;
```

The result from executing a query can be assigned to a variable by enclosing the query within back-tick (``) characters:

```
let $q = `select version()`;
```

- `ping`

Ping the server. This executes the `mysql_ping()` C API function. The function result is discarded. The effect is that if the connection has dropped and `reconnect` is enabled, pinging the server causes a reconnect.

- `query [statement]`

Send the statement to the server to be executed. The `query` command can be used to force `mysqltest` to send a statement to the server even if it begins with a keyword that is a `mysqltest` command.

- `query_horizontal statement`

Execute the statement and display its result horizontally.

```
query_horizontal select pi();
```

- `query_vertical statement`

Execute the statement and display its result vertically.

```
query_vertical select pi();
```

- `real_sleep num`

Sleep *num* seconds. *num* can have a fractional part. Unlike the `sleep` command, `real_sleep` is not affected by the `--sleep` command-line option.

```
--real_sleep 10
real_sleep 5;
```

Try not to use `sleep` or `real_sleep` commands more than necessary. The more of them there are, the slower the test suite becomes.

- `reap`

Receive the result of the statement most recently sent with the `send` command.

- `replace_column col_num value [col_num value] ...`

Replace strings in the output from the next statement. The value in *col\_num* is replaced by the corresponding *value*. There can be more than one *col\_num/value* pair. Column numbers start with 1.

A replacement value can be double-quoted. (Use ‘\”’ to specify a double quote within a replacement string.) Variables can be used in a replacement value if it is not double-quoted.

If mixed `replace_xxx` commands are given, only the final one applies.

Note: Although `replace_regex` and `replace_result` affect the output from `exec`, `replace_column` does not because `exec` output is not necessarily columnar.

```
--replace_column 9 #
replace_column 1 b 2 d;
```

- `replace_regex /pattern/replacement/[i] ...`

In the output from the next statement, find strings that match *pattern* (a regular expression) and replace them with *replacement*. Each instance of a string in the line that matches the pattern is replaced. Matching is case sensitive by default. Specify the optional *i* modifier to cause matching to be case insensitive.

The syntax for allowable patterns is the same as for the `REGEXP` SQL operator. In addition, the pattern can contain parentheses to mark substrings matched by parts of the pattern. These substrings can be referenced in the replacement string: An instance of `\N` in the replacement string causes insertion of the *N*-th substring matched by the pattern. For example, the following command matches `strawberry` and replaces it with `raspberry and strawberry`:

```
--replace_regex /(strawberry)/raspberry and \1/
```

Multiple `pattern/replacement` pairs may be given. The following command replaces instances of `A` with `C` (the first pattern replaces `A` with `B`, the second replaces `B` with `C`):

```
--replace_regex /A/B/ /B/C/
```

If a given pattern is not found, no error occurs and the input is unchanged.

The `replace_regex` command was added in MySQL 5.1.6.

- `replace_result from_val to_val [from_val to_val] ...`

Replace strings in the result. Each occurrence of `from_val` is replaced by the corresponding `to_val`. There can be more than `from_val/to_val` pair. Arguments can be quoted with single quotes or double quotes. Variable references within the arguments are expanded before replacement occurs. Values are matched literally. To use patterns, use the `replace_regex` command.

```
--replace_result 1024 MAX_KEY_LENGTH 3072 MAX_KEY_LENGTH
replace_result $MASTER_MYPORT MASTER_PORT;
```

- `require file_name`

This command specifies a file to be used for comparison against the results of the next query. If the contents of the file do not match or there is some other error, the test aborts with a “this test is not supported” error message.

```
--require r/slave-stopped.result
--require r/have_moscow_leap_timezone.require
```

- `result file_name`

This command specifies a file to be used for comparison when the test case completes. If the content does not match or there is some other error, write the result to `r/file_name.reject`.

If the `--record` command-line option is given, the `result` command changes the file by writing the ew test result to it.

- `rpl_probe`

Unknown.

- `save_master_pos`

For a master replication server, save the current binary log filename and position. These values can be used for subsequent `sync_with_master` or `sync_slave_with_master` commands.

- `send [statement]`

Send a statement to the server but do not wait for the result. The result must be received with the `reap` command.

If `statement` is omitted, the `send` command applies to the next statement executed. This means that `send` can be used on a line by itself before a statement. Thus, this command:

```
send select 1;
```

Is equivalent to these commands:

```
send;
select 1;
```

- `sleep num`

Sleep `num` seconds. `num` can have a fractional part. If the `--sleep` command-line option was given, the option value overrides the value given in the `sleep` command. For example, if `mysqltest`

is started with `--sleep=10`, the command `sleep 15` sleeps 10 seconds, not 15.

```
--real_sleep 10
real_sleep 5;
```

Try not to use `sleep` or `real_sleep` commands more than necessary. The more of them there are, the slower the test suite becomes.

- `source file_name`

Read test input from the named file.

If you find that several test case files contain a common section of commands (for example, statements that create a standard set of tables), you can put those commands in another file and those test cases that need the file can include it by means of a `source file_name` command. This enables you to write the code just once rather than in multiple test cases.

Normally, the filename in the `source` command is relative to the `mysql-test` directory because `mysqltest` usually is invoked in that directory.

A sourced file can use `source` to read other files, but take care to avoid a loop. The maximum nesting level is 16.

```
--source include/have_csv.inc
source include/varchar.inc;
```

- `start_timer`

Restart the timer, overriding any timer start that occurred earlier. By default, the timer starts when `mysqltest` begins execution.

- `sync_slave_with_master [connection_name]`

Executing this command is equivalent to executing the following commands:

```
save_master_pos;
connection connection_name;
sync_with_master 0;
```

If `connection_name` is not specified, the connection named `slave` is used.

The effect is to save the replication coordinates (binary log filename and position) for the server on the current connection (which is assumed to be a master replication server), and then switch to a slave server and wait until it catches up with the saved coordinates. Note that this command implicitly changes the current connection.

- `sync_with_master offset`

For a slave replication server, wait until it has caught up with the master. The position to synchronize to is the position saved by the most recent `save_master_pos` command plus `offset`.

To use this command, `save_master_pos` must have been executed at some point earlier in the test case to cause `mysqltest` to save the master's replication coordinates.

- `system command [arg] ...`

Execute the shell command using the `system()` library call. References to variables within the command are replaced with the corresponding values. Use `\$` to specify a literal `$` character.

On Cygwin, the command is executed from `cmd.exe`, so commands such as `rm` cannot be executed with `exec`. Use `system` instead.

```
--system echo '[mysqltest1]' > $MYSQLTEST_VARDIR/tmp/tmp.cnf
--system echo 'port=1234' >> $MYSQLTEST_VARDIR/tmp/tmp.cnf
system rm $MYSQLTEST_VARDIR/master-data/test/t1.MYI;
```

- `vertical_results`

Set the default query result display format to vertical. Initially, the default is to display results horizontally.

```
--vertical_results
```

- `wait_for_slave_to_stop`

Poll the current connection, which is assumed to be a connection to a slave replication server, by executing `SHOW STATUS LIKE 'Slave_running'` statements until the result is `OFF`.

- `while (expr)`

Begin a `while` loop block, which continues until an `end` line. `mysqltest` executes the block repeatedly as long as the expression is true. See flow-control constructs. [Section 5.4, “mysqltest Flow Control Constructs”](#), for further information about `while` statements.

Make sure that the loop includes some exit condition that eventually occurs. This can be done by writing `expr` so that it becomes false at some point.

```
let $i=5;
while ($i)
{
  echo $i;
  dec $i;
}
```

## 5.3. mysqltest Variables

You can define variables and refer to their values. You can also refer to environment variables, and there is a built-in variable that contains the result of the most recent SQL statement.

To define a variable, use the `let` command. Examples:

```
let $a = 14;
let $b = this is a string;
--let $a = 14
--let $b = this is a string
```

The variable name cannot contain whitespace or the '=' character.

If a variable has a numeric value, you can increment or decrement the value:

```
inc $a;
dec $a;
--inc $a
--dec $a
```

`inc` and `dec` are commonly used in `while` loops to modify the value of a counter variable that controls loop execution.

The result from executing a query can be assigned to a variable by enclosing the query within backtick (``) characters:

```
let $q = `select version()`;
```

References to variables can occur in the `echo`, `eval`, `exec`, and `system` commands. Variable references are replaced by their values. As of MySQL 5.0.26/5.1.12, the value assigned to a variable in a `let` command also can refer to variables.

You can refer to environment variables. For example, this command displays the value of the `$PATH` variable from the environment:

```
--echo $PATH
```

`$mysql_errno` is a built-in variable that contains the numeric error returned by the most recent SQL statement sent to the server, or 0 if the command executed successfully. `$mysql_errno` has a value of -1 if no statement has yet been sent.

`mysqltest` first checks `mysqltest` variables and then environment variables. `mysqltest` variable names are not case sensitive. Environment variable names are case sensitive.

## 5.4. mysqltest Flow Control Constructs

The syntax for `if` and `while` blocks looks like this:

```
if (expr)
{
  command list
}
```

```
while (expr)
{
  command list
}
```

An expression result is true if non-zero, false if zero. If the expression begins with `!`, the sense of the test is reversed.

There is no provision for `else` with `if`.

For a `while` loop, make sure that the loop includes some exit condition that eventually occurs. This can be done by writing `expr` so that it becomes false at some point.

The allowable syntax for `expr` is `$var_name`, `!$var_name`, a string or integer, or ``query``.

The opening `{` must be separated from the preceding `)` by whitespace (such as a space or a line break).

## 5.5. Error Handling

If an expected error is specified and that error occurs, `mysqltest` continues reading input. If the command is successful or a different error occurs, `mysqltest` aborts.

If no expected error is specified, `mysqltest` aborts unless the command is successful. (It is implicit that you expect `$mysql_errno` to be 0.)

By default, `mysqltest` aborts for certain conditions:



- A statement that fails when it should have succeeded. The following statement should succeed if table `t` exists;

```
select * from t;
```

- A statement that fails with an error different from that specified:

```
--error 1  
select * from no_such_table;
```

- A statement that succeeds when an error was expected:

```
--error 1  
select 'a string';
```

You can disable the abort for errors of the first type by using the `disable_abort_on_error` command. In this case, when errors occur for statements that should succeed, `mysqltest` continues processing input.

`disable_abort_on_error` does *not* cause `mysqltest` to ignore errors for the other two types, where you explicitly state which error you expect. This behavior is intentional. The rationale is that if you use the `error` command to specify an expected error, it is assumed that the test is sufficiently well characterized that only the specified error is acceptable.

If you do not use the `error` command, it is assumed that you might not know which error to expect or that it might be difficult to characterize all possible errors that could occur. In this case, `disable_abort_on_error` is useful for causing `mysqltest` to continue processing input. This can be helpful in the following circumstances:

- During test case development, it is useful to process all input even if errors occur so that you can see all errors at once, such as those that occur due to typographical or syntax errors. Otherwise, you can see and fix only one scripting problem at a time.
- Within a file that is included with a `source` command by several different test cases, errors might vary depending on the processing environment that is set up prior to the `source` command.
- Tests that follow a given statement that can fail are independent of that statement and do not depend on its result.

---

## Chapter 6. Creating and Executing Unit Tests

As of MySQL 5.1, storage engines and plugins can have unit tests to test their components. The top-level `Makefile` target `test-unit` run all unit tests: It scans the storage engine and plugin directories, the engines' and plugins' directories, recursively, and executes all executable files with a name that ends with `-t`.

The unit-testing facility is based on the MyTAP API. Each unit test must be written as a C or C++ program that obeys the MyTAP protocol and that is compiled to produce an executable with a name that ends with `-t`. For example, you can create a source file named `mytest-t.c` the compiles to produce an executable `mytest-t`. The executable will be found and run when you execute `make test` or `make test-unit` in the distribution top-level directory.

Example unit tests can be found in the `unittest/examples` directory of a MySQL source distribution. The code for the MyTAP protocol is located in the `unittest/mytap` directory.

Each unit test file should be stored in a storage engine or plugin directory (`storage/engine_name` or `plugin/plugin_name`), or one of its subdirectories. A reasonable convention is to create a `unittest` subdirectory under the storage engine or plugin directory and create unit test files in `unit-test`.

---

# Index

## A

abort-on-error option  
mysql-stress-test.pl, 36

## B

basedir option  
mysqltest, 19  
bench option  
mysql-test-run, 30  
mysql-test-run.pl, 22  
benchdir option  
mysql-test-run.pl, 22  
big option  
mysql-test-run, 30  
mysql-test-run.pl, 22  
big-test option  
mysqltest, 19

## C

check-testcases option  
mysql-test-run.pl, 22  
check-tests-file option  
mysql-stress-test.pl, 36  
cleanup option  
mysql-stress-test.pl, 36  
client-ddd option  
mysql-test-run.pl, 22  
client-debugger option  
mysql-test-run.pl, 22  
client-gdb option  
mysql-test-run, 30  
mysql-test-run.pl, 22  
comment option  
mysql-test-run, 30  
mysql-test-run.pl, 22  
compress option  
mysql-test-run, 30  
mysql-test-run.pl, 22  
mysqltest, 19  
cursor-protocol option  
mysql-test-run.pl, 22  
mysqltest, 19

## D

database option  
mysqltest, 19  
ddd option  
mysql-test-run, 30  
mysql-test-run.pl, 22  
debug option  
mysql-test-run, 30  
mysql-test-run.pl, 23  
mysqltest, 19

debugger option  
mysql-test-run.pl, 23  
do-test option  
mysql-test-run, 30  
mysql-test-run.pl, 23

## E

embedded-server option  
mysql-test-run, 30  
mysql-test-run.pl, 23  
extern option  
mysql-test-run, 30  
mysql-test-run.pl, 23

## F

fast option  
mysql-test-run, 30  
mysql-test-run.pl, 23  
force option  
mysql-test-run, 30  
mysql-test-run.pl, 23

## G

gcov option  
mysql-test-run, 30  
mysql-test-run.pl, 23  
gdb option  
mysql-test-run, 31  
mysql-test-run.pl, 23  
gprof option  
mysql-test-run, 31  
mysql-test-run.pl, 23

## H

help option  
mysql-stress-test.pl, 35  
mysql-test-run.pl, 22  
mysqltest, 18  
host option  
mysqltest, 19

## I

im-mysqld1-port option  
mysql-test-run.pl, 23  
im-mysqld2-port option  
mysql-test-run.pl, 23  
im-port option  
mysql-test-run.pl, 23  
include option  
mysqltest, 19

## L

local option  
mysql-test-run, 31  
local-master option  
mysql-test-run, 31

- log-error-details option
  - mysql-stress-test.pl, 36
- log-warnings option
  - mysql-test-run, 31
  - mysql-test-run.pl, 24
- loop-count option
  - mysql-stress-test.pl, 36
- M**
- manual-debug option
  - mysql-test-run.pl, 24
- manual-gdb option
  - mysql-test-run, 31
  - mysql-test-run.pl, 24
- master-binary option
  - mysql-test-run, 31
  - mysql-test-run.pl, 24
- master\_port option
  - mysql-test-run, 31
  - mysql-test-run.pl, 24
- max-connect-retries option
  - mysqltest, 19
- mysql-stress-test.pl
  - abort-on-error option, 36
  - check-tests-file option, 36
  - cleanup option, 36
  - help option, 35
  - log-error-details option, 36
  - loop-count option, 36
  - mysqltest option, 36
  - server-database option, 36
  - server-host option, 36
  - server-logs-dir option, 36
  - server-password option, 36
  - server-port option, 36
  - server-socket option, 36
  - server-user option, 36
  - sleep-time option, 36
  - stress-basedir option, 37
  - stress-datadir option, 37
  - stress-init-file option, 37
  - stress-mode option, 37
  - stress-suite-basedir option, 37
  - stress-tests-file option, 37
  - suite option, 37
  - test-count option, 37
  - test-duration option, 37
  - test-suffix option, 37
  - threads option, 37
  - verbose option, 37
- mysql-test-run
  - bench option, 30
  - big option, 30
  - client-gdb option, 30
  - comment option, 30
  - compress option, 30
  - ddd option, 30
  - debug option, 30
  - do-test option, 30
  - embedded-server option, 30
  - extern option, 30
  - fast option, 30
  - force option, 30
  - gcov option, 30
  - gdb option, 31
  - gprof option, 31
  - local option, 31
  - local-master option, 31
  - log-warnings option, 31
  - manual-gdb option, 31
  - master-binary option, 31
  - master\_port option, 31
  - mysqld option, 31
  - ndb-connectstring option, 31
  - ndb-connectstring-slave option, 31
  - ndb-extra-test option, 31
  - ndb-verbose option, 31
  - ndbcluster-port option, 32
  - ndbcluster-port-slave option, 32
  - ndbcluster\_port option, 32
  - ndbd-extra-opts option, 32
  - ndb\_mgm-extra-opts option, 31
  - ndb\_mgmd-extra-opts option, 32
  - old-master option, 32
  - ps-protocol option, 32
  - purify option, 32
  - record option, 32
  - skip-master-binlog option, 32
  - skip-ndb option, 32
  - skip-ndb-slave option, 32
  - skip-ndbcluster option, 32
  - skip-ndbcluster-slave option, 32
  - skip-rpl option, 32
  - skip-slave-binlog option, 32
  - skip-test option, 32
  - slave-binary option, 33
  - slave\_port option, 33
  - sleep option, 33
  - small-bench option, 33
  - socket option, 33
  - start-and-exit option, 33
  - start-from option, 33
  - strace-client option, 33
  - stress option, 33
  - stress-init-file option, 33
  - stress-loop-count option, 33
  - stress-mode option, 33
  - stress-suite option, 34
  - stress-test-count option, 34
  - stress-test-duration option, 34
  - stress-test-file option, 34
  - stress-threads option, 34
  - timer option, 34
  - tmpdir option, 34
  - use-old-data option, 34
  - user option, 34

- user-test option, 34
- valgrind option, 34
- valgrind-all option, 34
- valgrind-mysqctest option, 34
- valgrind-mysqctest-all option, 34
- valgrind-options option, 35
- wait-timeout option, 35
- warnings option, 35
- with-ndbcluster option, 35
- with-ndbcluster-all option, 35
- with-ndbcluster-only option, 35
- with-ndbcluster-slave option, 35
- with-openssl option, 35
- mysql-test-run.pl
  - bench option, 22
  - benchdir option, 22
  - big option, 22
  - check-testcases option, 22
  - client-ddd option, 22
  - client-debugger option, 22
  - client-gdb option, 22
  - comment option, 22
  - compress option, 22
  - cursor-protocol option, 22
  - ddd option, 22
  - debug option, 23
  - debugger option, 23
  - do-test option, 23
  - embedded-server option, 23
  - extern option, 23
  - fast option, 23
  - force option, 23
  - gcov option, 23
  - gdb option, 23
  - gprof option, 23
  - help option, 22
  - im-mysqld1-port option, 23
  - im-mysqld2-port option, 23
  - im-port option, 23
  - log-warnings option, 24
  - manual-debug option, 24
  - manual-gdb option, 24
  - master-binary option, 24
  - master\_port option, 24
  - mysqld option, 24
  - ndb-connectstring option, 24
  - ndb-connectstring-slave option, 24
  - ndb-extra-test option, 24
  - ndbcluster-port option, 24
  - ndbcluster-port-slave option, 24
  - ndbcluster\_port option, 24
  - netware option, 24
  - notimer option, 24
  - ps-protocol option, 24
  - record option, 25
  - reorder option, 25
  - script-debug option, 25
  - skip-im option, 25
  - skip-master-binlog option, 25
  - skip-ndb option, 25
  - skip-ndb-slave option, 25
  - skip-ndbcluster option, 25
  - skip-ndbcluster-slave option, 25
  - skip-rpl option, 25
  - skip-slave-binlog option, 25
  - skip-ssl option, 25
  - skip-test option, 25
  - slave-binary option, 25
  - slave\_port option, 25
  - sleep option, 26
  - small-bench option, 26
  - socket option, 26
  - sp-protocol option, 26
  - ssl option, 26
  - start-and-exit option, 26
  - start-dirty option, 26
  - start-from option, 26
  - strace-client option, 26
  - stress option, 26
  - stress-init-file option, 26
  - stress-loop-count option, 26
  - stress-mode option, 26
  - stress-suite option, 27
  - stress-test-count option, 27
  - stress-test-duration option, 27
  - stress-test-file option, 27
  - stress-threads option, 27
  - suite option, 27
  - suite-timeout option, 27
  - testcase-timeout option, 27
  - timer option, 27
  - tmpdir option, 27
  - unified-diff option, 27
  - use-old-data option, 27
  - user option, 27
  - user-test option, 27
  - valgrind option, 27
  - valgrind-all option, 28
  - valgrind-mysqctest option, 28
  - valgrind-mysqctest-all option, 28
  - valgrind-options option, 28
  - valgrind-path option, 28
  - vardir option, 28
  - view-protocol option, 28
  - wait-timeout option, 28
  - warnings option, 28
  - with-ndbcluster option, 28
  - with-ndbcluster-all option, 28
  - with-ndbcluster-only option, 28
  - with-ndbcluster-slave option, 28
  - with-openssl option, 28
- mysqld option
  - mysql-test-run, 31
  - mysql-test-run.pl, 24
- mysqctest
  - basedir option, 19

- big-test option, 19
  - compress option, 19
  - cursor-protocol option, 19
  - database option, 19
  - debug option, 19
  - help option, 18
  - host option, 19
  - include option, 19
  - max-connect-retries option, 19
  - no-defaults option, 19
  - password option, 19
  - port option, 19
  - ps-protocol option, 19
  - quiet option, 20
  - record option, 20
  - result-file option, 20
  - server-arg option, 20
  - server-file option, 20
  - silent option, 20, 20
  - skip-safemalloc option, 20
  - sleep option, 20
  - socket option, 20
  - sp-protocol option, 20
  - test-file option, 21
  - timer-file option, 21
  - tmpdir option, 21
  - user option, 21
  - verbose option, 21
  - version option, 21
  - view-protocol option, 21
  - mysqltest option
    - mysql-stress-test.pl, 36
- N**
- ndb-connectstring option
    - mysql-test-run, 31
    - mysql-test-run.pl, 24
  - ndb-connectstring-slave option
    - mysql-test-run, 31
    - mysql-test-run.pl, 24
  - ndb-extra-test option
    - mysql-test-run, 31
    - mysql-test-run.pl, 24
  - ndb-verbose option
    - mysql-test-run, 31
  - ndbcluster-port option
    - mysql-test-run, 32
    - mysql-test-run.pl, 24
  - ndbcluster-port-slave option
    - mysql-test-run, 32
    - mysql-test-run.pl, 24
  - ndbcluster\_port option
    - mysql-test-run, 32
    - mysql-test-run.pl, 24
  - ndbd-extra-opts option
    - mysql-test-run, 32
  - ndb\_mgm-extra-opts option
    - mysql-test-run, 31
  - ndb\_mgmd-extra-opts option
    - mysql-test-run, 32
  - netware option
    - mysql-test-run.pl, 24
  - no-defaults option
    - mysqltest, 19
  - notimer option
    - mysql-test-run.pl, 24
- O**
- old-master option
    - mysql-test-run, 32
- P**
- password option
    - mysqltest, 19
  - port option
    - mysqltest, 19
  - ps-protocol option
    - mysql-test-run, 32
    - mysql-test-run.pl, 24
    - mysqltest, 19
  - purify option
    - mysql-test-run, 32
- Q**
- quiet option
    - mysqltest, 20
- R**
- record option
    - mysql-test-run, 32
    - mysql-test-run.pl, 25
    - mysqltest, 20
  - reorder option
    - mysql-test-run.pl, 25
  - result-file option
    - mysqltest, 20
- S**
- script-debug option
    - mysql-test-run.pl, 25
  - server-arg option
    - mysqltest, 20
  - server-database option
    - mysql-stress-test.pl, 36
  - server-file option
    - mysqltest, 20
  - server-host option
    - mysql-stress-test.pl, 36
  - server-logs-dir option
    - mysql-stress-test.pl, 36
  - server-password option
    - mysql-stress-test.pl, 36
  - server-port option
    - mysql-stress-test.pl, 36

- server-socket option
    - mysql-stress-test.pl, 36
  - server-user option
    - mysql-stress-test.pl, 36
  - silent option
    - mysqltest, 20, 20
  - skip-im option
    - mysql-test-run.pl, 25
  - skip-master-binlog option
    - mysql-test-run, 32
    - mysql-test-run.pl, 25
  - skip-ndb option
    - mysql-test-run, 32
    - mysql-test-run.pl, 25
  - skip-ndb-slave option
    - mysql-test-run, 32
    - mysql-test-run.pl, 25
  - skip-ndbcluster option
    - mysql-test-run, 32
    - mysql-test-run.pl, 25
  - skip-ndbcluster-slave option
    - mysql-test-run, 32
    - mysql-test-run.pl, 25
  - skip-rpl option
    - mysql-test-run, 32
    - mysql-test-run.pl, 25
  - skip-safemalloc option
    - mysqltest, 20
  - skip-slave-binlog option
    - mysql-test-run, 32
    - mysql-test-run.pl, 25
  - skip-ssl option
    - mysql-test-run.pl, 25
  - skip-test option
    - mysql-test-run, 32
    - mysql-test-run.pl, 25
  - slave-binary option
    - mysql-test-run, 33
    - mysql-test-run.pl, 25
  - slave\_port option
    - mysql-test-run, 33
    - mysql-test-run.pl, 25
  - sleep option
    - mysql-test-run, 33
    - mysql-test-run.pl, 26
    - mysqltest, 20
  - sleep-time option
    - mysql-stress-test.pl, 36
  - small-bench option
    - mysql-test-run, 33
    - mysql-test-run.pl, 26
  - socket option
    - mysql-test-run, 33
    - mysql-test-run.pl, 26
    - mysqltest, 20
  - sp-protocol option
    - mysql-test-run.pl, 26
    - mysqltest, 20
  - ssl option
    - mysql-test-run.pl, 26
  - start-and-exit option
    - mysql-test-run, 33
    - mysql-test-run.pl, 26
  - start-dirty option
    - mysql-test-run.pl, 26
  - start-from option
    - mysql-test-run, 33
    - mysql-test-run.pl, 26
  - strace-client option
    - mysql-test-run, 33
    - mysql-test-run.pl, 26
  - stress option
    - mysql-test-run, 33
    - mysql-test-run.pl, 26
  - stress-basedir option
    - mysql-stress-test.pl, 37
  - stress-datadir option
    - mysql-stress-test.pl, 37
  - stress-init-file option
    - mysql-stress-test.pl, 37
    - mysql-test-run, 33
    - mysql-test-run.pl, 26
  - stress-loop-count option
    - mysql-test-run, 33
    - mysql-test-run.pl, 26
  - stress-mode option
    - mysql-stress-test.pl, 37
    - mysql-test-run, 33
    - mysql-test-run.pl, 26
  - stress-suite option
    - mysql-test-run, 34
    - mysql-test-run.pl, 27
  - stress-suite-basedir option
    - mysql-stress-test.pl, 37
  - stress-test-count option
    - mysql-test-run, 34
    - mysql-test-run.pl, 27
  - stress-test-duration option
    - mysql-test-run, 34
    - mysql-test-run.pl, 27
  - stress-test-file option
    - mysql-test-run, 34
    - mysql-test-run.pl, 27
  - stress-tests-file option
    - mysql-stress-test.pl, 37
  - stress-threads option
    - mysql-test-run, 34
    - mysql-test-run.pl, 27
  - suite option
    - mysql-stress-test.pl, 37
    - mysql-test-run.pl, 27
  - suite-timeout option
    - mysql-test-run.pl, 27
- T**
- test cases, 1

---

- test framework, 3
- test-count option
  - mysql-stress-test.pl, 37
- test-duration option
  - mysql-stress-test.pl, 37
- test-file option
  - mysqltest, 21
- test-suffix option
  - mysql-stress-test.pl, 37
- testcase-timeout option
  - mysql-test-run.pl, 27
- threads option
  - mysql-stress-test.pl, 37
- timer option
  - mysql-test-run, 34
  - mysql-test-run.pl, 27
- timer-file option
  - mysqltest, 21
- tmpdir option
  - mysql-test-run, 34
  - mysql-test-run.pl, 27
  - mysqltest, 21

## U

- unified-diff option
  - mysql-test-run.pl, 27
- unit tests, 1, 3, 53
- use-old-data option
  - mysql-test-run, 34
  - mysql-test-run.pl, 27
- user option
  - mysql-test-run, 34
  - mysql-test-run.pl, 27
  - mysqltest, 21
- user-test option
  - mysql-test-run, 34
  - mysql-test-run.pl, 27

## V

- valgrind option
  - mysql-test-run, 34
  - mysql-test-run.pl, 27
- valgrind-all option
  - mysql-test-run, 34
  - mysql-test-run.pl, 28
- valgrind-mysqltest option
  - mysql-test-run, 34
  - mysql-test-run.pl, 28
- valgrind-mysqltest-all option
  - mysql-test-run, 34
  - mysql-test-run.pl, 28
- valgrind-options option
  - mysql-test-run, 35
  - mysql-test-run.pl, 28
- valgrind-path option
  - mysql-test-run.pl, 28
- vardir option
  - mysql-test-run.pl, 28

- verbose option
  - mysql-stress-test.pl, 37
  - mysqltest, 21
- version option
  - mysqltest, 21
- view-protocol option
  - mysql-test-run.pl, 28
  - mysqltest, 21

## W

- wait-timeout option
  - mysql-test-run, 35
  - mysql-test-run.pl, 28
- warnings option
  - mysql-test-run, 35
  - mysql-test-run.pl, 28
- with-ndbcluster option
  - mysql-test-run, 35
  - mysql-test-run.pl, 28
- with-ndbcluster-all option
  - mysql-test-run, 35
  - mysql-test-run.pl, 28
- with-ndbcluster-only option
  - mysql-test-run, 35
  - mysql-test-run.pl, 28
- with-ndbcluster-slave option
  - mysql-test-run, 35
  - mysql-test-run.pl, 28
- with-openssl option
  - mysql-test-run, 35
  - mysql-test-run.pl, 28