



DRILL TABLE					UNIT=INCH
SYMBOL	DIA	TOOL	PLATED	COUNT	
.	0.009	T09	YES	802	
.	0.014	T10	YES	5	
.	0.031	T02	YES	16	
.	0.032	T03	YES	24	
.	0.035	T04	YES	7	
.	0.036	T06	YES	3	
.	0.047	T01	YES	2	
.	0.055	T05	YES	10	
.	0.062	T08	NO	2	
⊗	0.165	T07	NO	1	
Totals:		872 holes.	869 Plated	3 Unplated	

LAYER ORDER		
—	Top Silkscreen	top_silk.grb
—	Top Soldermask	top_mask.grb
—	Top Signal	top_copper.grb
▨	Inner 1 Signal	inner_copper_1.grb
▨	Inner 2 Signal	inner_copper_2.grb
▨	Inner 3 Signal	inner_copper_3.grb
▨	Inner 4 Signal	inner_copper_4.grb
▨	Inner 5 Signal	inner_copper_5.grb
▨	Inner 6 Signal	inner_copper_6.grb
—	Bottom Signal	bottom_copper.grb
—	Bottom Soldermask	bottom_mask.grb
—	Bottom Silkscreen	bottom_silk.grb

0.060

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES		CONTRACT NO. _____	The XYZ COMMUNICATIONS CO. A DIVISION OF ABC BLDG COMPANY PASADENA, CA 91234 RELEASED THROUGH EDWG
DECIMALS	ANGLES	PREPARED BY: NTC IN COMPLIANCE WITH XYZ D-20478 VOLUME 11 DSMS 813-203, VOLUME 1	
.XX ± .03 .XXX ± .010	±1/2°	APVD: _____ DATE: 18 AUG 06	C3I Comm Adapter Fabrication Drawing
MACHINE FINISH	✓	CHK: _____	
DO NOT SCALE DRAWING INTERPRET DRAWING PER ASME Y14.100M		STRU: _____	SIZE: D 12345 9XXXXXX REV: B
MATERIAL		REF: _____	
XYZ USER (DOCUMENT)	NEXT ASSEMBLY	USED ON	SCALE: 2:1 UNCLASSIFIED SHEET 1 OF 1
	APPLICATION		